

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW03 CLIMB TO 3000 DIRECT HITON AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 213.36 INBOUND. CHART FAS OBST: 1295 TOWER 392631N/0835313W CHART BUCKEYE MOA DINNE TO RW03: 3.04/40
SINRE (IAF)	NEKOE (NOPT) (FB)	123.16 / 5.00	3000	
CUSTA (IAF)	NEKOE (NOPT) (FB)	303.28 / 5.00	3000	
NEKOE (IF/IAF)	DINNE (FB)	033.22 / 6.51	2600	

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- HOLD SW NEKOE, RT, 033.22 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 033.26 FAF: DINNE DIST FAF TO MAP: 4.75 THLD: 4.75
- MIN. ALT: NEKOE 3000, DINNE 2600
- DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
- MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
- GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR
- MSA FROM: _____

MAG VAR: 5W

EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X											
CATEGORY =====>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	1600	1	567	1600	1	567	1600	1 1/2	567		NA					
CIRCLING	1740	1	707	1740	1	707	1740	2	707		NA					

NOTES:

CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE WILMINGTON/AIRBOURNE AIRPARK ALTIMETER SETTING AND INCREASE ALL MDAS 20 FEET.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: PROCEDURE NA AT NIGHT.

SEE 8260-10

CITY AND STATE WILMINGTON, OH	ELEVATION: 1033 TDZE: 1033 AIRPORT NAME: CLINTON FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO.: RNAV (GPS) RWY 3, ORIG JUL -5 2007	SUP: AMDT: NONE DATED
---	---	-------------------------------------	--	------------------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

TAA

	FROM	TO	ALT
1.	303/30 CW 123/30 (NOPT)	NEKOE (IF/IAF) (FB)	3000
2.	123/30 CW 213/30	SINRE (IAF) (FB)	3000
3.	213/30 CW 303/30	CUSTA (IAF) (FB)	3000

CITY AND STATE

WILMINGTON, OH

ELEVATION: 1033 TDZE: 1033

AIRPORT NAME:

CLINTON FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 3, ORIG

JUL - 5 2007

SUP:

AMDT:

NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
WP	12345678901	23456789012	34567890123	45678901234	56789012345	67890123456	78901234567	89012345678	90123456789	01234567890	12345678901	23456789012	34567890123

[illegible][illegible][illegible]

CITY AND STATE WILMINGTON, OH	ELEVATION: 1033 TDZE: 1033 AIRPORT NAME: CLINTON FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO.: RNAV (GPS) RWY 3, ORIG JUL -5 2007	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	CUSTA	CUSTA	010	IAF	IF		FB				
	CUSTA	NEKOE	020		TF		FB	1.0	303.3 (298T)	005.0	03000
	SINRE	SINRE	010	IAF	IF		FB				
	SINRE	NEKOE	020		TF		FB	1.0	123.2 (118T)	005.0	03000
	NEKOE	NEKOE	010		HF	R	FB		033.2 (028T)	005.0	03000
		NEKOE	010	FACF	IF		FB				03000
		DINNE	020	FAF	TF		FB	0.5	033.2 (028T)	006.5	02600
		RW03	030	MAP	TF		FO	0.3	033.3 (028T)	004.8	01066

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	033.3 (028T)		01433
	HITON	050		DF		FO	1.0			03000
	HITON	060		HM	R	FO	2.0	213.4 (208T)	005.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CUSTA	N391735.60	W0835310.91	N3917.593	W08353.182
	DINNE	N392542.04	W0835453.13	N3925.701	W08354.886
	HITON	N394005.96	W0834452.02	N3940.099	W08344.867
	NEKOE	N391957.72	W0835851.40	N3919.962	W08358.857
	SINRE	N392219.56	W0840432.28	N3922.326	W08404.538
	RW03	N392953.35	W0835158.74	N3929.889	W08351.979

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW03	01026	40

CITY AND STATE
WILMINGTON, OH

ELEVATION: 1033 TDZE: 1033
 AIRPORT NAME:
 CLINTON FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:
 RNAV (GPS) RWY 3, ORIG
 JUL -5 2007

SUP:
 AMDT: NONE
 DATED: