

**Federal Aviation
Administration**

Transmittal Letter 19-16

June 14, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	AL	Brewton	Brewton Muni	9/5073	6/4/2019	RNAV (GPS) RWY 30, Orig

AIRAC Date: 18 July 2019

FDC 9/5073 12J IAP BREWTON MUNI, Brewton, AL. RNAV (GPS) RWY 30, ORIG... DELETE CIRCLING MINIMUMS. MISSED APPROACH: CLIMB TO 2000 DIRECT EHEBA AND ON TRACK 215 TO ODAZO AND HOLD. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: FOR UNCOMPENSATED BARO/VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 48C. DELETE NOTE: FOR UNCOMPENSATED BARO/VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). CHART NOTE: RWY 30 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. MINIMUMS: LNAV CAT C VISIBILITY 1 5/8 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PENSACOLA ALTIMETER SETTING; INCREASE LPV DA TO 611 FEET; INCREASE LNAV/VNAV DA TO 787 FEET; INCREASE ALL MDAS 100 FEET; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CATS C AND D VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PENSACOLA ALTIMETER SETTING AND INCREASE ALL DA 84 FEET AND ALL MDA 100 FEET, INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS, LNAV AND CIRCLNG CATS C AND D VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) RWY 30, ORIG-A. 1905291233-PERM