

**Federal Aviation  
Administration**

**Transmittal Letter 19-16**

**June 14, 2019**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	MI	Bad Axe	Huron County Memorial	9/5428	6/3/2019	RNAV (GPS) RWY 35, Orig-B

**AIRAC Date: 18 July 2019**

FDC 9/5428 BAX IAP HURON COUNTY MEMORIAL, Bad Axe, MI. RNAV (GPS) RWY 35, ORIG-B... CHART NOTE:  
FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16 C OR ABOVE 54 C. CHART  
NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MBS INTL ALTIMETER SETTING AND  
INCREASE ALL DA 129 FEET AND ALL MDA 140 FEET; INCREASE LPV ALL CATS AND LNAV CAT C  
VISIBILITY 3/8 MILE. PBN REQUIREMENTS NOTE: RNP APCH. DELETE CIRCLING MINIMUMS. DELETE  
NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MBS  
INTL ALTIMETER SETTING AND INCREASE ALL DA 129 FEET AND ALL MDA 140 FEET; INCREASE LPV ALL  
CATS AND LNAV CAT C VISIBILITY 3/8 MILE; INCREASE CIRCLING CAT C VISIBILITY 1/2 MILE. THIS IS  
RNAV (GPS) RWY 35, ORIG-C. 1905291651-PERM