

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES																	MISSED APPROACH									
FROM				TO				COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW31R CLIMB TO 3000 DIRECT ZOTWY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 131.32 INBOUND. CHART FAS OBST: 241 TREE 394712N/1215051W CHART FAS OBST: 347 TOWER 394557N/1214925W DISTANCE TO THLD FROM 250 HAT: 0.69 NM. CHART VDP AT 1.06 NM TO RW31R* *LNAV ONLY. WAAS CHANNEL # 77912 REFERENCE PATH ID: W31A LTP HAE: 35.8 M												
GRIDD				KLEMM (TF) (FB) (RNP 2.00)				028.94 / 14.58				3000														
KLEMM (IAF)				UNJED (TF) (FB) (RNP 1.00)				311.58 / 9.10				3000														
UNJED (IF)				DIANS (TF) (FB) (RNP 1.00)				311.51 / 6.01				2000														
DIANS (FAF)				STARW/2.50 NM TO RW31R (TF) (FB) (RNP 0.30)				311.47 / 2.89																		
STARW/2.50 NM TO RW31R				RW31R (MAP) (TF) (FO) (RNP 0.30)				311.47 / 2.50																		
(SEE FORM 8260-10)																										
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT UNJED 3. FAC: 311.47 FAF: DIANS DIST FAF TO MAP: 5.39 THLD: 5.39 4. MIN. ALT: UNJED 3000, DIANS 2000, STARW/2.50 NM TO RW31R 1060* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2000 GS ALT AT: DIANS 2000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS CLEAR 8. MSA FROM: RW31R 8300																	MAG VAR: 16E EPOCH YEAR: 1990									
MINIMUMS																										
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT																	ALTERNATE: N A			STANDARD						
CATEGORY =====>		A			B			C			D			E												
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA											
LPV DA	476	1	250	476	1	250	476	1	250	476	1	250														
LNAV/VNAV DA	733	1 3/4	507	733	1 3/4	507	733	1 3/4	507	733	1 3/4	507														
LNAV MDA	600	1	374	600	1	374	600	1	374	600	1 1/4	374														
CIRCLING	640	1	400	700	1	460	700	1 1/2	460	800	2	560														
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: CIRCLING NA E OF RWY 13L/31R. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GRIDD ON V23 AND T261 SOUTHEAST BOUND.																										
CITY AND STATE				ELEVATION: 240 TDZE: 226				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:										
CHICO, CA				AIRPORT NAME: CHICO MUNI								RNAV (GPS) RWY 31R, ORIG-C 1 FEBRUARY 2018				AMDT: ORIG-B										
																DATED 08/17/2017										

QUALITY
 10
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW31R (MAP)	476 MSL (CA)	311.47	
476 MSL	ZOTWY (DF) (FO) (RNP 1.00)		3000

CITY AND STATE
CHICO, CA

ELEVATION: 240 TDZE: 226
AIRPORT NAME:
CHICO MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 31R, ORIG-C
1 FEBRUARY 2018

SUP: **QUALITY 10 CHECKED**
AMDT: ORIG-B
DATED: 08/17/2017

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCIC
RUNWAY	RW31R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W31A
LTP/FTP LATITUDE	394716.1780N
LTP/FTP LONGITUDE	1215104.4520W
LTP/FTP ELLIPSOIDAL HEIGHT	+00358
FPAP LATITUDE	394831.3200N
FPAP LONGITUDE	1215206.6900W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0704
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

D7E8086A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+00632
FPAP ORTHOMETRIC HEIGHT	+00632

CITY AND STATE

CHICO, CA

ELEVATION: 240

TDZE: 226

AIRPORT NAME:

CHICO MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 31R, ORIG-C

1 FEBRUARY 2018

SUP:

AMDT:

DATED:

 QUALITY
10

CHECKED

ORIG-B

08/17/2017