

**Federal Aviation  
Administration**

**Transmittal Letter 19-16**

**June 14, 2019**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	AZ	Glendale	Glendale Muni	9/5165	6/3/2019	RNAV (GPS) RWY 19, Amdt 2A

**AIRAC Date: 18 July 2019**

FDC 9/5165 GEU IAP GLENDALE MUNI, Glendale, AZ. RNAV (GPS) RWY 19, AMDT 2A... DELETE CIRCLING MINIMUMS. MINIMUMS: LNAV CAT C VISIBILITY 1 3/8 SM. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 47C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 47C (116F). PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: RWY 19 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. DELETE NOTE: CIRCLING NA WEST OF RWY 1-19. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PHOENIX SKY HARBOR INTL ALTIMETER SETTING: INCREASE LPV DA TO 1384 FEET; INCREASE LNAV/VNAV DA TO 1617 FEET AND ALL CATS VISIBILITY 1/4 SM; INCREASE ALL MDA 60 FEET AND LNAV CAT C AND D VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PHOENIX SKY HARBOR INTL ALTIMETER SETTING AND INCREASE ALL DA 45 FEET AND MDA 60 FEET AND INCREASE LNAV/VNAV ALL CATS AND LNAV CAT C AND D AND CIRCLING CAT C VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) RWY 19, AMDT 2B. 1905291322-PERM