

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW36						
LEPER		JOPRO (TF) (FO) (RNP 2.00)		186.46 / 54.63				3000		CLIMB TO 3000 DIRECT CAYRA AND HOLD.						
HELMS		CICAP (TF) (FB) (RNP 2.00)		284.14 / 30.93				3000								
CICAP (IAF)		JOPRO (NOPT) (TF) (FB) (RNP 1.00)		269.62 / 5.00				3000		ADDITIONAL FLIGHT DATA: HOLD N, RT, 179.56 INBOUND. CHART FAS OBST: 394 TREE 362242N/0903928W CHART VDP AT 1.15 NM TO RW36. WAPUR TO RW36: 3.05/40.						
HARIB (IAF)		JOPRO (NOPT) (TF) (FB) (RNP 1.00)		089.49 / 5.68				3000								
JOPRO (IF/IAF) (SEE FORM 8260-10)		WAPUR (TF) (FB) (RNP 1.00)		359.56 / 7.34				2000								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD S JOPRO, RT, 359.56 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																
3. FAC: 359.56 FAF: WAPUR DIST FAF TO MAP: 5.16 THLD: 5.16																
4. MIN. ALT: JOPRO 3000, WAPUR 2000																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																
8. MSA FROM: RW36 2500																
MAG VAR: 1E EPOCH YEAR: 1995																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD				
CATEGORY ==>		A		B		C		D		E						
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA		700	1	407	700	1	407	700	1 1/4	407		NA				
CIRCLING		760	1	467	760	1	467	760	1 1/2	467		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VDP NA WHEN USING WALNUT RIDGE ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WALNUT RIDGE ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET. INCREASE LNAV CAT C VISIBILITY 1/8 MILE. (CONTINUED ON PAGE 2)																
CITY AND STATE CORNING, AR		ELEVATION: 293 TDZE: 293 AIRPORT NAME: CORNING MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG-B 17 AUGUST 2017						SUP: AMDT: ORIG-A DATED 04/02/2015				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
WAPUR (FAF)	RW36 (MAP) (TF) (FO) (RNP 0.30)	359.56 / 5.16	
RW36 (MAP)	693 MSL (CA)	359.56	
693 MSL	CAYRA (DF) (FO) (RNP 1.00)		3000

NOTES, (CONT.):

CHART NOTE: RWY 36 HELICOPTER VISIBILITY REDUCTION BELOW 1 3/4 SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HARIB ON V305 SOUTHWEST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HELMS ON V140 EASTBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT LEPER ON V175 NORTHWEST BOUND AND V69 NORTHBOUND.

QUALITY
10
CHECKED

CITY AND STATE CORNING, AR	ELEVATION: 293	TDZE: 293	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG-B 17 AUGUST 2017	SUP:	
	AIRPORT NAME:				AMDT:	ORIG-A
	CORNING MUNI				DATED:	04/02/2015