

**Federal Aviation
Administration**

Transmittal Letter 19-16

June 14, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	ME	Millinocket	Millinocket Muni	9/5064	6/4/2019	RNAV (GPS) RWY 11, Orig-A

AIRAC Date: 18 July 2019

FDC 9/5064 MLT IAP MILLINOCKET MUNI, Millinocket, ME. RNAV (GPS) RWY 11, ORIG-A... DELETE CIRCLING MINIMUMS. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 41C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 41C (105F). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOULTON ALTIMETER SETTING AND INCREASE ALL DA AND MDA 120 FEET; INCREASE LPV AND LNAV/VNAV VISIBILITY ALL CATS 1/2 SM AND LNAV VISIBILITY CAT B 1/4 SM AND CAT C/D 1/2 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOULTON ALTIMETER SETTING AND INCREASE ALL DA AND MDA 120 FEET; INCREASE LPV AND LNAV/VNAV VISIBILITY ALL CATS 1/2 MILE, LNAV VISIBILITY CAT B 1/4 MILE AND CAT C/D 1/2 MILE; AND CIRCLING VISIBILITY CAT A/B 1/4 MILE AND CAT C/D 1/2 MILE. CHART NOTE: RWY 11 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 11, ORIG-B. 1905291224-PERM