

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION												
TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW36 LNAV: RW36 CLIMB TO 2300 DIRECT ISUVE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 183.94 INBOUND. CHART FAS OBST: 209 TREE 273005N/0815232W CHART FAS OBST: 172 TWR 272817N/0815232W WAAS CHANNEL # 62929 REFERENCE PATH ID: W36A WANUM TO RW36: 3.00/33. CHART SARASOTA/BRADENTON INTL ASOS. LTP HAE: 6.5 M								
BRDGE	JOXOB (FB)	136.75 / 11.69	2000									
JOXOB (IAF)	ITUYA (NOPT) (FB)	093.90 / 5.00	2000									
RINSE (IAF)	ITUYA (NOPT) (FB)	298.12 / 16.85	2000									
ITUYA (IF/IAF)	WANUM (FB)	003.94 / 6.11	1800									
WANUM (FAF)	XASEF/2.60 NM TO RW36 (FB)	003.94 / 2.62										
XASEF/2.60 NM TO RW36 (SEE FORM 8260-10)	RW36 (MAP) (FO)	003.94 / 2.60										
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 4W EPOCH YEAR: 2000								
2. HOLD S ITUYA, RT, 003.94 INBOUND, 2000 FT. IN LIEU OF PT (IAF)												
3. FAC: 003.94 FAF: WANUM DIST FAF TO MAP: 5.22 THLD: 5.22												
4. MIN. ALT: ITUYA 2000, WANUM 1800, XASEF/2.60 NM TO RW36 960												
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>												
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>												
7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR												
8. MSA FROM: RW36 2800												
MINIMUMS												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X								
CATEGORY =====>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	520	1	417	520	1	417	520	1 1/8	417		NA	
LNAV MDA	560	1	457	560	1	457	560	1 3/8	457		NA	
CIRCLING	620	1	512	620	1	512	620	1 1/2	512		NA	
NOTES: CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 18 NA AT NIGHT. CHART NOTE: USE SARASOTA/BRADENTON INT ALTIMETER SETTING; WHEN NOT RECEIVED, USE TAMPA INTL ALTIMETER SETTING AND INCREASE ALL MDA 20 FT, INCREASE LP CAT C VISIBILITY 1/8 MILE. CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 36 PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)												
CITY AND STATE		ELEVATION: 108 THRE: 103		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
WAUCHULA, FL		AIRPORT NAME:		RNAV		RNAV (GPS) RWY 36, AMDT 1 26 JULY 2012			AMDT: ORIG			
		WAUCHULA MUNI							DATED 01/18/2007			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW36 (MAP)	508 MSL	003.94	
508 MSL	ISUVE (FO)		2300

NOTES, (CONT.):

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BRDGE ON V97-482 NORTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RINSE ON V157-521 SOUTHEAST BOUND.

CHART PLANVIEW NOTE AT JOXOB: MAX 210 KIAS.

QUALITY
CHECKED

CITY AND STATE

WAUCHULA, FL

ELEVATION: 108

THRE: 103

AIRPORT NAME:

WAUCHULA MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 36, AMDT 1

26 JULY 2012

SUP:

AMDT: ORIG

DATED: 01/18/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCHN
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	W36A
REFERENCE PATH IDENTIFIER (APPROACH ID)	273033.8350N
LTP/FTP LATITUDE	0815249.6405W
LTP/FTP LONGITUDE	+00065
LTP/FTP ELLIPSOIDAL HEIGHT	273203.1900N
FPAP LATITUDE	0815249.7400W
FPAP LONGITUDE	00033.3
THRESHOLD CROSSING HEIGHT (TCH)	F
TCH UNITS SELECTOR (METERS OR FEET USED)	03.00
GLIDEPATH ANGLE (GPA)	106.75
COURSE WIDTH AT THRESHOLD	1528
LENGTH OFFSET	40.0
HORIZONTAL ALERT LIMIT (HAL)	0.0
VERTICAL ALERT LIMIT (VAL)	

CRC REMAINDER

55DEE80E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00315
FPAP ORTHOMETRIC HEIGHT	+00315

CITY AND STATE

WAUCHULA, FL

ELEVATION: 108

THRE: 103

AIRPORT NAME:

WAUCHULA MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 36, AMDT 1

26 JULY 2012

SUP:

AMDT:

ORIG

DATED:

01/18/2007



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KCHNK7FR36	ABRDGE	010BRDGEK7EA0E	IF						18000		A JS	
SUSAP	KCHNK7FR36	ABRDGE	020JOXOBK7EA0E	A 020TF		13680117		+ 02000				A JS	
SUSAP	KCHNK7FR36	ABRDGE	030ITUYAK7EA0EE	B 010TF		09390050		+ 02000				A JS	
SUSAP	KCHNK7FR36	AITUYA	010ITUYAK7EA0EE	AR HF		00390040		+ 02000		18000		A JS	
SUSAP	KCHNK7FR36	ARINSE	010RINSEK7EA0E	A IF						18000		A JS	
SUSAP	KCHNK7FR36	ARINSE	020ITUYAK7EA0EE	B 010TF		29810169		+ 02000				A JS	
SUSAP	KCHNK7FR36	R	010ITUYAK7EA0E	I IF				+ 02000		18000		A JS	
SUSAP	KCHNK7FR36	R	020WANUMK7EA1E	F 051TF		00390061		+ 01800			RW36	K7PGA JS	
SUSAP	KCHNK7FR36	R	020WANUMK7EA2WALP		N	ALNAV						JS	
SUSAP	KCHNK7FR36	R	021XASEFK7EA0E	S 031TF		00390026		V 0096000965		-300		A JS	
SUSAP	KCHNK7FR36	R	030RW36 K7PG0GY	M 031TF		00390026		00137		-300		A JS	
SUSAP	KCHNK7FR36	R	040	0 M CA		0039		+ 00508				A JS	
SUSAP	KCHNK7FR36	R	050ISUVEK7EA0EY	DF				+ 02300				A JS	
SUSAP	KCHNK7FR36	R	060ISUVEK7EA0EE	R HM		18390040		+ 02300				A JS	

[illegible]

CITY AND STATE WAUCHULA, FL	ELEVATION: 108	THRE: 103	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 26 JULY 2012	SUP: RNAV
	AIRPORT NAME: WAUCHULA MUNI				AMDT: ORIG
					DATED: 01/18/2007

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	HECKE
AMDT:	ORIG
DATED:	01/18/2007



U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	BRDGE	BRDGE	010		IF		FB					
	BRDGE	JOXOB	020	IAF	TF		FB	2.0	136.8(132.8T)	011.7	AA 02000	
	BRDGE	ITUYA	030		TF		FB	1.0	093.9(089.9T)	005.0	AA 02000	
	ITUYA	ITUYA	010	IAF	HF	R	FO		003.9(359.9T)	004.0	AA 02000	
	RINSE	RINSE	010	IAF	IF		FB					
	RINSE	ITUYA	020		TF		FB	1.0	298.1(294.1T)	016.9	AA 02000	
		ITUYA	010	FACF	IF		FB				AA 02000	
		WANUM	020	FAF	TF		FB	0.5	003.9(359.9T)	006.1	AA 01800	
		XASEF	021	SDF	TF		FB	0.3	003.9(359.9T)	002.6	AA 00960	GS 00965
		RW36	030	MAP	TF		FO	0.3	003.9(359.9T)	002.6	AT 00137	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		003.9(359.9T)		AA 00508	
	ISUVE	050		DF		FO				AA 02300	
	ISUVE	060		HM	R	FO		183.9(179.9T)	004.0	AA 02300	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	BRDGE	N272709.30	W0820803.74	N2727.155	W08208.062
	ISUVE	N274234.57	W0815250.49	N2742.576	W08152.842
	ITUYA	N271912.13	W0815248.84	N2719.202	W08152.814
	JOXOB	N271911.70	W0815825.66	N2719.195	W08158.428
	RINSE	N271218.85	W0813532.79	N2712.314	W08135.547
	WANUM	N272519.56	W0815249.27	N2725.326	W08152.821
	XASEF	N272757.41	W0815249.46	N2727.957	W08152.824
	RW36	N273033.84	W0815249.64	N2730.564	W08152.827

RUNWAY DATA	THRESHOLD	ELEVATION	TCH
RWY			
RW36	00103		33

QUALITY
2

CITY AND STATE WAUCHULA, FL	ELEVATION: 108 THRE: 103	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 26 JULY 2012	SUP:
	AIRPORT NAME: WAUCHULA MUNI			AMDT: ORIG
				DATED: 01/18/2007