

# RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
IVUVE (IAF)	NUTFO (NOPT) (FB)	201.81 / 5.00	3400	LNAV: RW11
JISBO (IAF)	NUTFO (NOPT) (FB)	021.71 / 5.00	3400	
NUTFO (IF/IAF)	LUGTE (FB)	111.76 / 6.10	3300	CLIMB TO 3300 DIRECT IGIDY AND HOLD.
LUGTE (FAF)	IPOWU/2.20 NM TO RW11 (FB)	111.86 / 2.92		
IPOWU/2.20 NM TO RW11	RW11 (MAP) (FO)	111.91 / 2.20		
RW11 (MAP)	1980 MSL	111.91		
1980 MSL	IGIDY (FO)		3300	ADDITIONAL FLIGHT DATA: HOLD E, RT, 292.12 INBOUND. CHART FAS OBST: 1719 TREE 474808N/0995653W LUGTE TO RW11: 3.04/40.

MAG VAR: 8E EPOCH YEAR: 2000

[illegible]

QUALITY  
&  
CHECKED

FAA FORM 8260 - 3 / April 2006 (computer generated)

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED; USE DEVIL'S LAKE ALTIMETER SETTING AND INCREASE ALL MDA 140 FEET; INCREASE LNAV CAT C VISIBILITY 1/2 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	022/30 CW 202/30 (NOPT)	022/5 CW 202/5	3900
2.	022/5 CW 202/5	NUTFO (IF/IAF) (FB)	3400
3.	202/30 CW 292/30	IVUVE (IAF) (FB)	3400
4.	292/30 CW 022/30	JISBO (IAF) (FB)	3800

QUALITY  
9  
CHECKED

CITY AND STATE HARVEY, ND	ELEVATION: 1607 TDZE: 1607 AIRPORT NAME: HARVEY MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 11, ORIG 23 SEP 2010	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

QUALITY  
&  
CHECKED

ELEVATION: 1607 TDZE: 1607  
AIRPORT NAME:  
HARVEY MUNI

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 11, ORIG  
23 SEP 2010

SUP:	
AMDT:	NONE
DATED:	