

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
RITOE (IAF)	ZEGRA (NOPT) (FB)	085.26 / 5.00	2500	LPV: DA LNAV/VNAV: DA LNAV: RW35 CLIMB TO 2500 DIRECT JETBI AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 175.32 INBOUND. CHART FAS OBST: 809 TREE 335515N/0962358W CHART FAS OBST: 819 TREE 335603N/0962406W DISTANCE TO THLD FROM 250 HAT: 0.63 NM. CHART VDP AT 1.14 MILES TO RW35* *LNAV ONLY. WAAS CHANNEL # 48918 REFERENCE PATH ID: W35A
TUPLE (IAF)	ZEGRA (NOPT) (FB)	265.37 / 5.00	2500	
ZEGRA (IF/IAF)	WOVAM (FB)	355.32 / 6.10	2500	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S ZEGRA, RT, 355.32 INBOUND, 2500 FT. IN LIEU OF PT (IAF)
- FAC: 355.32 FAF: WOVAM DIST FAF TO MAP: 5.45 THLD: 5.45
- MIN. ALT: ZEGRA 2500, WOVAM 2500, PAMMI/1.70 NM TO RW35 1280*
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2500 GS ALT AT: WOVAM 2500 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 48.0 34:1 IS CLEAR
- MSA FROM:

MAG VAR: 5E EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A					STANDARD @						
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	940	3/4	250	940	3/4	250	940	3/4	250							
LNAV/VNAV DA	1111	1 1/2	421	1111	1 1/2	421	1111	1 1/2	421							
LNAV MDA	1100	1	410	1100	1	410	1100	1 1/4	410							
CIRCLING	1220	1	521	1220	1	521	1220	1 1/2	521			NA				

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING ARDMORE MUNI ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 *LNAV ONLY
 SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
CHECKED

CITY AND STATE	ELEVATION: 699 TDZE: 690	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
DURANT, OK	AIRPORT NAME:	RNAV	RNAV (GPS) RWY 35, AMDT 1	AMDT: ORIG
	EAKER FIELD		29 JUL 2010	DATED 07/10/2003

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ARDMORE MUNI ALTIMETER SETTING AND INCREASE ALL DA 96 FEET, ALL MDA 100 FEET; INCREASE LPV CATS A,B,C VISIBILITY 1/2 MILE, INCREASE LNAV/VNAV CATS A,B,C AND LNAV AND CIRCLING CAT C VISIBILITY 1/4 MILE.

CHART NOTE: VDP NA WITH ARDMORE MUNI ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	265/30 CW 085/30 (NOPT)	265/10 CW 085/10	3800
2.	265/10 CW 085/10	ZEGRA (IF/IAF) (FB)	2500
3.	085/30 CW 175/30	085/10 CW 175/10	3600
4.	085/10 CW 175/10	RITOE (IAF) (FB)	2500
5.	175/30 CW 265/30	TUPLE (IAF) (FB)	2500

QUALITY
CHECKED

CITY AND STATE

DURANT, OK

ELEVATION: 699 TDZE: 690

AIRPORT NAME:

EAKER FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 1

29 JUL 2010

SUP:

AMDT: ORIG

DATED: 07/10/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KDUA
RUNWAY RW35
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W35A
LTP/FTP LATITUDE 335607.0835N
LTP/FTP LONGITUDE 0962342.3235W
LTP/FTP ELLIPSOIDAL HEIGHT +01839
FPAP LATITUDE 335736.3400N
FPAP LONGITUDE 0962341.7200W
THRESHOLD CROSSING HEIGHT (TCH) 00048.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1224
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

3F4DA127

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K4
LTP ORTHOMETRIC HEIGHT +02104
FPAP ORTHOMETRIC HEIGHT +02104

QUALITY
A
CHECKED

CITY AND STATE

DURANT, OK

ELEVATION: 699 TDZE: 690

AIRPORT NAME:

EAKER FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 1

29 JUL 2010

SUP:

AMDT: ORIG

DATED: 07/10/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
A
CHECKED

CITY AND STATE DURANT, OK	ELEVATION: 699 TDZE: 690 AIRPORT NAME: EAKER FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 29 JUL 2010	SUP:
				AMDT: ORIG
				DATED: 07/10/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1 2 3 4 5 6 7 8 9 0 1 2 3
PP 1234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KDUAK4PR35 RW35 001 0000W35A0N3356070835W09623423235+018390300N3357363400W09623417200106751224000480F4005003F4DA127
SUSAP KDUAK4PR35 RW35 002E +02104+02104LPV 48918

QUALITY
A
CHECKED

CITY AND STATE

DURANT, OK

ELEVATION: 699

TDZE: 690

AIRPORT NAME:

EAKER FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 1

29 JUL 2010

SUP:

AMDT:

ORIG

DATED:

07/10/2003