

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
GULLI	AHOBY (FO)	343.16 / 34.46	3100	LPV: DA LNAV/VNAV: DA LNAV: RW17 CLIMB TO 3000 DIRECT HIGH AND ON TRACK 192.04 TO YUPUD AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 011.99 INBOUND. CHART FAS OBST: 1109 TREE 362442N/0971704W CHART VANCE 1B MOA. DISTANCE TO THLD FROM 250 HATH: 0.67 NM. WAAS CHANNEL # 72921 REFERENCE PATH ID: W17A LTP HAE: 268.4 M
PER VORTAC (IAF)	AHOBY (NOPT) (FB)	203.32 / 11.67	3000	
WOPEK (IAF)	AHOBY (NOPT) (FB)	103.62 / 8.60	3000	
AHOBY (IF/IAF)	BUGPY (FB)	173.72 / 6.04	2600	
BUGPY (FAF)	CUXOP/1.60 NM TO RW17 (FB)	173.72 / 3.39		
CUXOP/1.60 NM TO RW17 (SEE FORM 8260-10)	RW17 (MAP) (FO)	173.72 / 1.60		

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD N AHOBY, LT, 173.72 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
3. FAC: 173.72 FAF: BUGPY DIST FAF TO MAP: 4.99 THLD: 4.99
4. MIN. ALT: AHOBY 3000, BUGPY 2600, CUXOP/1.60 NM TO RW17 1520*
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: 2600 GS ALT AT: BUGPY 2600 OM: MM: IM:
7. GS ANGLE: 3.00 TCH: 37.0 34:1 IS NOT CLEAR
8. MSA FROM: RW17 3200

MAG VAR: 6E

EPOCH YEAR: 1995

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1224	1	250	1224	1	250	1224	1	250		NA				
LNAV/VNAV DA	1414	1 1/2	440	1414	1 1/2	440	1414	1 1/2	440		NA				
LNAV MDA	1360	1	386	1360	1	386	1360	1 1/8	386		NA				
CIRCLING	1480	1	478	1480	1	478	1480	1 1/2	478		NA				

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING KPNC ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F).
 CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 17 PROCEDURE NA AT NIGHT.
 CHART NOTE: DME/DME RNP-0.3 NA.
 (SEE FORM 8260-10)

CITY AND STATE PERRY, OK	ELEVATION: 1002 THRE: 974 AIRPORT NAME: PERRY MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG 30 JUN 2011	SUP:
				AMDT: NONE
				DATED

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW17 (MAP)	1224 MSL	173.72	
1224 MSL	HIGIY (FB)		
HIGIY	YUPUD (FO)	192.04 / 11.16	3000

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GULLI ON V140 EASTBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON PER VORTAC AIRWAY RADIALS 129 CW 291.

*LNAV ONLY

CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE PONCA CITY ALTIMETER SETTING AND INCREASE ALL DA 53 FEET, ALL MDA 60 FEET AND INCREASE LNAV/VNAV ALL CATS AND LNAV CAT C VISIBILITY 1/4 MILE.

CHART PLANVIEW NOTE: RADAR REQUIRED FOR ARRIVALS AT WOPEK.

QUALITY
9
CHECKED

CITY AND STATE
 PERRY, OK

ELEVATION: 1002 **THRE:** 974
AIRPORT NAME:
 PERRY MUNI

FACILITY IDENTIFIER:
 RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 17, ORIG
 30 JUN 2011

SUP:
AMDT: NONE
DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER F22
RUNWAY RW17
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR 0
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W17A
LTP/FTP LATITUDE 362333.4285N
LTP/FTP LONGITUDE 0971638.1500W
LTP/FTP ELLIPSOIDAL HEIGHT +02684
FPAP LATITUDE 362204.2100N
FPAP LONGITUDE 0971637.6100W
THRESHOLD CROSSING HEIGHT (TCH) 00037.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1192
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

227B9ACD

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K4
LTP ORTHOMETRIC HEIGHT +02968
FPAP ORTHOMETRIC HEIGHT +02968

CITY AND STATE

PERRY, OK

ELEVATION: 1002

THRE: 974

AIRPORT NAME:

PERRY MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, ORIG

30 JUN 2011

SUP:

AMDT:

NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE PERRY, OK	ELEVATION: 1002 THRE: 974 AIRPORT NAME: PERRY MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG 30 JUN 2011	SUP:
				AMDT: NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

QUALITY
CHECKED

CITY AND STATE PERRY, OK	ELEVATION: 1002 THRE: 974 AIRPORT NAME: PERRY MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG 30 JUN 2011	SUP:
				AMDT: NONE
				DATED: