

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES							MISSED APPROACH										
FROM			TO			COURSE AND DISTANCE	ALTITUDE										
HENAB (IAF)			DROWE (NOPT) (FB)			138.92 / 6.00	5600	LPV: DA LNAV: RW23 CLIMB TO 6000 DIRECT YATUB AND VIA TRACK 291.97 TO KENYA AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 100.57 INBOUND. CHART FAS OBST: 3353 TREE 372205N/0811018W DISTANCE TO THLD FROM 300 HAT: 0.71 NM. CHART VDP AT 2.28 MILES TO RW23* *LNAV ONLY. WAAS CHANNEL # 50207 REFERENCE PATH ID: W23A									
FOMOP (IAF)			DROWE (NOPT) (FB)			319.02 / 6.00	5600										
DROWE (IF/IAF)			COLES (FB)			228.97 / 6.28	4600										
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE DROWE, RT, 228.97 INBOUND, 5600 FT. IN LIEU OF PT (IAF) 3. FAC: 228.92 FAF: COLES DIST FAF TO MAP: 5.22 THLD: 5.22 4. MIN. ALT: DROWE 5600, COLES 4600 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 4600 GS ALT AT: COLES OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 58.0 34:1 IS NOT CLEAR 8. MSA FROM: _____																	
MAG VAR: 7W EPOCH YEAR: 2010																	
MINIMUMS																	
TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A		STANDARD @										
CATEGORY =====>	A			B			C			D			E				
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	3142	1	300	3142	1	300	3142	1	300	3142	1	300					
LNAV MDA	3640	1	798	3640	1 1/4	798	3640	2 1/4	798	3640	2 1/2	798					
CIRCLING	3640	1	783	3640	1 1/4	783	3640	2 1/4	783	3640	2 1/2	783					
NOTES:																	
CHART NOTE: DME/DME RNP-0.3 NA.																	
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.																	
CHART NOTE: CIRCLING NA SE RWY 5-23.																	
CHART NOTE: VDP NA WHEN USING BECKLEY ALTIMETER SETTING.																	
SEE 8260-10																	
CITY AND STATE				ELEVATION: 2857 TDZE: 2842				FACILITY IDENTIFIER:				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:	
BLUEFIELD, WV				AIRPORT NAME:				RNAV				RNAV (GPS) RWY 23, ORIG				AMDT: NONE	
				MERCER COUNTY								11 FEB 2010				DATED	

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BECKLEY ALTIMETER SETTING AND INCREASE DA TO 3585 FT AND ALL MDA TO 4100 FT; INCREASE LPV ALL CATS VISIBILITY 1 1/2 MILE, INCREASE LNAV AND CIRCLING VISIBILITY CATS A AND B 1/4 MILE, CAT C 3/4 MILE, CAT D 1/2 MILE.

TAA

	FROM	TO	ALT
1.	139/30 CW 319/30 (NOPT)	139/10 CW 319/10	7000
2.	139/10 CW 319/10	DROWE (IF/IAF) (FB)	5600
3.	319/30 CW 049/30	FOMOP (IAF) (FB)	7000
4.	049/30 CW 139/30	HENAB (IAF) (FB)	7000

QUALITY
6
CHECKED

CITY AND STATE

BLUEFIELD, WV

ELEVATION: 2857 TDZE: 2842

AIRPORT NAME:

MERCER COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 23, ORIG

11 FEB 2010

SUP:

AMDT: NONE

DATED:

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBLF
RUNWAY	RW23
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W23A
LTP/FTP LATITUDE	371802.8700N
LTP/FTP LONGITUDE	0811207.4800W
LTP/FTP ELLIPSOIDAL HEIGHT	+08398
FPAP LATITUDE	371727.9600N
FPAP LONGITUDE	0811246.6500W
THRESHOLD CROSSING HEIGHT (TCH)	00058.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	80.00
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

B306B153

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+08706
FPAP ORTHOMETRIC HEIGHT	+08706

QUALITY
CHECKED

CITY AND STATE

BLUEFIELD, WV

ELEVATION: 2857 TDZE: 2842

AIRPORT NAME:

MERCER COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 23, ORIG

11 FEB 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KBLFK6FR23	ADROWE	010DROWEK6EA0EE	AR	HF		22900050	+	05600	18000		A	JS
SUSAP	KBLFK6FR23	AFOMOP	010FOMOPK6EA0E	A	IF					18000		A	JS
SUSAP	KBLFK6FR23	AFOMOP	020DROWEK6EA0EE	B	010TF		31900060	+	05600			A	JS
SUSAP	KBLFK6FR23	AHENAB	010HENABK6EA0E	A	IF					18000		A	JS
SUSAP	KBLFK6FR23	AHENAB	020DROWEK6EA0EE	B	010TF		13890060	+	05600			A	JS
SUSAP	KBLFK6FR23	R	010DROWEK6EA0E	I	IF			+	05600	18000		A	JS
SUSAP	KBLFK6FR23	R	020COLESK6EA1E	F	051TF		22900063	+	04600			A	JS
SUSAP	KBLFK6FR23	R	020COLESK6EA2WALPV			N	ALNAV						JS
SUSAP	KBLFK6FR23	R	030RW23 K6PG0GY	M	031TF		22890052		02914	-300		A	JS
SUSAP	KBLFK6FR23	R	040YATUBK6EA0E	M	010DF							A	JS
SUSAP	KBLFK6FR23	R	050KENYAK6EA0EY		010TF		2920	+	06000			A	JS
SUSAP	KBLFK6FR23	R	060KENYAK6EA0EE		R020HM		10060050	+	06000			A	JS

[illegible]

SUP:	
AMDT:	NONE
DATED:	

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE BLUEFIELD, WV	ELEVATION: 2857 TDZE: 2842 AIRPORT NAME: MERCER COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 23, ORIG 11 FEB 2010	SUP:
				AMDT: NONE
				DATED: