

**Federal Aviation
Administration**

Transmittal Letter 19-16

June 14, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	MO	Dexter	Dexter Muni	9/5020	6/4/2019	RNAV (GPS) RWY 36, Amdt 1A

AIRAC Date: 18 July 2019

FDC 9/5020 DXE IAP DEXTER MUNI, Dexter, MO. RNAV (GPS) RWY 36, AMDT 1A... DELETE CIRCLING MINIMUMS. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE POPLAR BLUFF ALTIMETER SETTING, WHEN NOT RECEIVED USE CAPE GIRARDEAU RGNL ALTIMETER SETTING AND INCREASE ALL DA 33 FEET AND ALL MDA 40 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 SM, INCREASE LNAV CATS C/D VISIBILITY 1/4 SM. DELETE NOTE: USE POPLAR BLUFF ALTIMETER SETTING, WHEN NOT RECEIVED USE CAPE GIRARDEAU RGNL ALTIMETER SETTING AND INCREASE ALL DA 33 FEET AND ALL MDA 40 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE, INCREASE LNAV AND CIRCLING CATS C/D VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) RWY 36, AMDT 1B. 1905291201-PERM