

**Federal Aviation
Administration**

Transmittal Letter 19-25

October 18, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/5/2019	GA	Gainesville	Lee Gilmer Memorial	9/5873	9/26/2019	RNAV (GPS) RWY 23, Amdt 1

AIRAC Date: 5 DECEMBER 2019

FDC 9/5873 GVL IAP LEE GILMER MEMORIAL, Gainesville, GA. RNAV (GPS) RWY 23, AMDT 1... DELETE TDZE: 1272. DELETE APT ELEV: 1276. CHART TDZE: 1274. CHART APT ELEV: 1277. LPV DA 1722 ALL CATS. LNAV/VNAV DA 1884 ALL CATS. LNAV HAT 566 ALL CATS. CIRCLING HAA CATS A, B, C 603, CAT D 783. CHART NOTE: CIRCLING RWY 11, 29 NA AT NIGHT. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 46C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 46C (114F). CHART NOTE: RWY 23 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ANNYE ON V463 NORTHBOUND AND V415 WESTBOUND. DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ANNYE VIA V463 NORTHBOUND AND V415 WESTBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT IRMOS ON V5-51-267-417 SOUTHBOUND. DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT IRMOS VIA V5-51-267-417 SOUTHBOUND. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JEFFERSON ALTIMETER SETTING: INCREASE ALL DA/MDA 80 FEET; INCREASE LPV ALL CATS VISIBILITY 1/4 SM

AND INCREASE LNAV CATS C/D VISIBILITY AND CIRCLING CATS C/D VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JEFFERSON ALTIMETER SETTING AND INCREASE ALL DAS/MDAS 80 FEET, LPV ALL CATS VISIBILITY 1/4 MILE, LNAV CATS C AND D 1/4 MILE AND CIRCLING CATS C AND D 1/4 MILE. MISSED APPROACH: CLIMB TO 4000 DIRECT ZADIT AND ON 200 TRACK TO WOMAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000. THIS IS RNAV (GPS) RWY 23, AMDT 1A. 1909091734-PERM