

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
VOR/DME										STANDARD INSTRUMENT APPROACH PROCEDURE									
										FLIGHT STANDARDS SERVICE - FAR PART 97. 23									
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE				ALTITUDE		MAP: GIRSE / 11.87 DME								
ROD VORTAC		ZEDIN / 24.80 DME			068.89/24.80				4000		CLIMB TO 3000 DIRECT ROD VORTAC AND HOLD								
ZEDIN (IF/IAF)		DUVEC / 16.87 DME			248.89/7.93 (ROD R-069)				3000										
NOPT FOR ARRIVALS AT ZEDIN		ON V144 NORTHWESTBOUND.									ADDITIONAL FLIGHT DATA: HOLD W, RT, 068.49 INBOUND. FAS OBST: 1508 TWR 402254/0834527 CHART: 1624 TWR 402205/0834402 CADAY TO GIRSE: 3.46/41 CHART VDP AT 13.94 DME DISTANCE VDP TO THLD 2.06 MILES FAC CROSSES RWY C/L EXTENDED 61 FROM THLD. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. PAPI, REIL, MIRL RWY 7/25								
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)										MAG VAR: 5 W EPOCH YEAR: 1985									
2. HOLD <u>E</u> ZEDIN, RT, 248.89 INBOUND, 4000 FT IN LIEU OF PT (IAF)																			
3. FAC <u>248.89</u> FAF <u>DUVEC</u> DIST FAF TO MAP <u> </u> - THLD <u>5.00</u>																			
4. MIN. ALT <u>ZEDIN 4000, DUVEC 3000, CADAY/ 14.70 DME 2100</u>																			
8. MSA FROM: ROD VORTAC 330-190 3000, 190-330 2600																			
MINIMUMS																			
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		X										
CATEGORY	A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-25	1820	1	697	1820	1	697	1820	2	697	1820	2 1/4	697							
CIRCLING	1820	1	697	1820	1	697	1820	2	697	1820	2 1/4	697							
JAMES M. COX DAYTON INTL ALTIMETER SETTING MINIMUMS																			
S-25	1920	1	797	1920	1 1/4	797	1920	2 1/4	797	1920	2 1/2	797							
CIRCLING	1920	1	797	1920	1 1/4	797	1920	2 1/4	797	1920	2 1/2	797							
NOTES: OBTAIN LOCAL ALTIMETER ON CTAF; WHEN NOT RECEIVED USE JAMES M. COX DAYTON INTL ALTIMETER SETTING. VDP NA WITH JAMES M. COX DAYTON INTL ALTIMETER SETTING.																			
CITY AND STATE		ELEVATION: 1123 TDZE: 1123		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP									
BELLEFONTAINE, OH		BELLEFONTAINE REGIONAL		ROD		MAR 20 2003 VOR/DME RWY 25, ORIG				AMDT NONE									
										DATE									