

**Federal Aviation
Administration**

Transmittal Letter 20-04

December 27, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/30/2020	FL	Orlando	Orlando Sanford Intl	9/0518	12/16/2019	RNAV (GPS) RWY 9L, Amdt 3A

AIRAC Date: 30 JANUARY 2020

FDC 9/0518 SFB IAP ORLANDO SANFORD INTL, ORLANDO, FL. RNAV (GPS) RWY 9L, AMDT 3A... DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C (-2F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW 0C OR ABOVE 54C. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EXECUTIVE ALTIMETER SETTING AND INCREASE ALL DA 43 FEET AND ALL MDA 60 FEET; INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE AND LNAV CAT C,D VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EXECUTIVE ALTIMETER SETTING AND INCREASE LPV DA TO 282, LNAV/VNAV DA TO 501 AND ALL MDA 60 FEET; INCREASE LNAV/VNAV ALL CATS VISIBILITIES 1/8 SM AND LNAV CAT C/D VISIBILITY 1/4 SM. DELETE NOTE: DME/DME RNP-0.3 NA. EQUIPMENT REQUIREMENTS NOTE: RNP APCH. CHART CIRCLING ICON. CIRCLING CAT C MDA 600/HAA 545, CAT D MDA 640/HAA 585. THIS IS RNAV (GPS) RWY 9L, AMDT 3B. 1912021357-PERM