

**Federal Aviation
Administration**

Transmittal Letter 22-03

December 10, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/27/2022	TX	Victoria	Victoria Rgnl	1/5742	9/24/2021	ILS OR LOC RWY 13, Orig

AIRAC Date: 27 JANUARY 2022

FDC 1/5742 VCT IAP VICTORIA RGNL, VICTORIA, TX. ILS OR LOC RWY 13, ORIG... CHART PLANVIEW
NOTE: PROCEDURE NA FOR ARRIVAL ON PSX VORTAC AIRWAY RADIALS 218 CW 233. CHART PROFILE
NOTE: USE I-VCT DME WHEN ON THE LOCALIZER COURSE. DELETE NOTE: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE PORT LAVACA ALTIMETER SETTING: INCREASE S-ILS DA TO 367 FEET;
INCREASE ALL MDAS 60 FEET AND VISIBILITY CATS C AND D 1/4 SM, CAT E 1/8 SM. DELETE NOTE: FOR
INOPERATIVE ALS, WHEN USING PORT LAVACA ALTIMETER SETTING, INCREASE S-ILS 13 CAT E
VISIBILITY TO 3/4 SM AND S-LOC 13 CAT C/D/E VISIBILITY TO 1 1/8 SM. DELETE NOTE: VDP NA WHEN
USING PORT LAVACA ALTIMETER SETTING. ALTERNATE MINIMUMS: ILS: STANDARD - NA WHEN LOCAL
WEATHER NOT AVAILABLE, NA WHEN CONTROL TOWER CLOSED; LOC: STANDARD - CAT D 800-2 1/2, NA
WHEN LOCAL WEATHER NOT AVAILABLE, NA WHEN CONTROL TOWER CLOSED. THIS IS ILS OR LOC
RWY 13, ORIG-A. 2109101400-PERM