

**Federal Aviation
Administration**

Transmittal Letter 20-10

March 20, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

| AIRAC DATE | STATE | CITY | AIRPORT | FDC NUMBER | FDC DATE | SUBJECT |
|------------|-------|--------------|----------------------|------------|-----------|--------------------|
| 4/23/2020 | IA | Marshalltown | Marshalltown Muni | 0/4970 | 3/11/2020 | VOR RWY 13, Amdt 2 |

AIRAC Date: 23 APRIL 2020

FDC 0/4970 MIW IAP MARSHALLTOWN MUNI, MARSHALLTOWN, IA. VOR RWY 13, AMDT 2... CHART AIRPORT ELEVATION 975 MSL. CHART CIRCLING ICON. CIRCLING CAT D MDA 1840/HAA 865. VIS CAT C 1 3/4 SM, CAT D 2 3/4 SM. JURSI FIX MINIMUMS: CIRCLING CAT C MDA 1460/HAA 485, CAT D MDA 1840/HAA 865. VIS CAT D 2 3/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GRINNEL ALTIMETER SETTING AND INCREASE ALL MDA 80 FT; INCREASE S-13 CAT C AND D AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GRINNEL ALTIMETER SETTING AND INCREASE ALL MDA 80 FT; INCREASE S-13 CAT C/D VISIBILITY 1/4 SM AND CIRCLING CAT C VISIBILITY 1/8 SM AND CAT D VISIBILITY 1/4 SM, INCREASE JURSI FIX MINIMUMS CIRCLING CAT D VISIBILITY 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 900-2 3/4. THIS IS VOR RWY 13, AMDT 2A. 2003101447-PERM