

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES										MISSED APPROACH										
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: 3.63 MILES AFTER SHY VOR/DME OR AT 3.63 DME FIX									
VIH VOR/DME			SHY VOR/DME			255.17 / 42.96			3100		CLIMB TO 3100 THEN RIGHT TURN DIRECT SHY VOR/DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 037.04 INBOUND. CHART FAS OBST: 1006 TREE 380257N/0923413W 1129 AAO 380201N/0923457W. SHY VOR/DME TO RW04: 3.07/55.									
ROACH INT/SGF 57.85 DME			SHY VOR/DME			143.36 / 12.40			3100											
SGF VORTAC (IAF)			WYLEY INT/SHY 9.75 DME (NOPT)			036.89 / 44.07			3100											
WYLEY INT/SHY 9.75 DME (IF)			SHY VOR/DME			036.96 / 9.78			2100											
1. PT <u>L</u> SIDE OF COURSE <u>217.05</u> OUTBOUND <u>3100</u> FT WITHIN <u>10</u> MILES OF <u>SHY VOR/DME</u> (IAF) 2. _____ 3. FAC <u>037.05</u> FAF <u>SHY VOR/DME</u> DIST FAF TO MAP <u>3.63</u> THLD <u>3.63</u> 4. MIN. ALT <u>SHY VOR/DME 2100</u> 8. MSA FROM: <u>SHY VOR/DME 3100</u>										MAG VAR: 0E EPOCH YEAR: 2015										
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @								
CATEGORY ==>		A			B			C			D			E						
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-4		1260	1	397	1260	1	397	1260	1 1/8	397		NA								
CIRCLING		1320	1	451	1320	1	451	1380	1 1/2	511		NA								
NOTES: CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON SGF VORTAC AIRWAY RADIALS 024 CW 075. CHART NOTE: STRAIGHT-IN MINIMUMS NA AT NIGHT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CAMDENTON ALTIMETER SETTING AND INCREASE ALL MDA 60 FT AND S-4 CAT C VISIBILITY 1/4 MILE.																				
CITY AND STATE		ELEVATION: 869		THRE: 863		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP								
KAISER LAKE OZARK, MO		AIRPORT NAME:		LEE C FINE MEMORIAL		SHY		VOR RWY 4, AMDT 7A				AMDT 7								
								22 AUGUST 2013				DATE 05/02/2013								

