

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.														
TERMINAL ROUTES											MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW33 CLIMB TO 3000 DIRECT GOCRE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 150.46 INBOUND. CHART FAS OBST: 1109 TREE 414526N/0960959W 1222 AAO 414243N/0960808W DISTANCE TO THLD FROM 250 HAT: 0.66 NM. CHART VDP AT 0.93 NM TO RW33* *LNAV ONLY. WAAS CHANNEL # 62940 REFERENCE PATH ID: W33A CHART CIRCLING ICON. LTP HAE: 284.7 M									
BRAVA (IF/IAF)		ANISY (TF) (FB) (RNP 1.00)			330.62 / 6.00				2500											
ANISY (FAF)		OTEKE/3.00 NM TO RW33 (TF) (FB) (RNP 0.30)			330.58 / 1.51															
OTEKE/3.00 NM TO RW33		RW33 (MAP) (TF) (FO) (RNP 0.30)			330.58 / 3.00															
RW33 (MAP)		1276 MSL			330.58				3000											
1276 MSL		GOCRE (DF) (FO) (RNP 1.00)																		
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SE BRAVA, RT, 330.62 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 330.58 FAF: ANISY _____ DIST FAF TO MAP: 4.51 THLD: 4.51 4. MIN. ALT: BRAVA 3000, ANISY 2500, OTEKE/3.00 NM TO RW33 2020* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2500 GS ALT AT: ANISY 2500 _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR 8. MSA FROM: _____																	MAG VAR: 3E		EPOCH YEAR: 2020	
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT											ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
LPV DA	1276	7/8	250	1276	7/8	250	1276	7/8	250		NA									
LNAV/VNAV DA	1281	7/8	255	1281	7/8	255	1281	7/8	255		NA									
LNAV MDA	1360	1	334	1360	1	334	1360	1	334		NA									
CIRCLING	1420	1	393	1480	1	453	1760	2 1/4	733		NA									
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -22C (-7F) OR ABOVE 54C @ CAT C 800-2 1/4 (130F). CHART NOTE: DME/DME RNP-0.3 NA.																				
CITY AND STATE		ELEVATION: 1027 TDZE: 1026			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP: RNAV (GPS) RWY 32									
TEKAMAH, NE		AIRPORT NAME: TEKAMAH MUNI					RNAV (GPS) RWY 33, AMDT 1				AMDT: ORIG									
							30 MARCH 2017				DATED 10/25/2007									



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	241/30 CW 061/30 (NOPT) 241/15 CW 061/15	241/15 CW 061/15 BRAVA (IF/IAF) (FB)	3600 3000
2.	061/30 CW 241/30	BRAVA (IF/IAF) (FO)	3100

QUALITY
16
CHECKED

CITY AND STATE TEKAMAH, NE	ELEVATION: 1027 TDZE: 1026 AIRPORT NAME: TEKAMAH MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 33, AMDT 1 30 MARCH 2017	SUP: RNAV (GPS) RWY 32
				AMDT: ORIG
				DATED: 10/25/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KTQE
RUNWAY	RW33
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W33A
LTP/FTP LATITUDE	414531.0365N
LTP/FTP LONGITUDE	0961028.8175W
LTP/FTP ELLIPSOIDAL HEIGHT	+02847
FPAP LATITUDE	414650.8435N
FPAP LONGITUDE	0961121.8640W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1536
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

7510EF2A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+03121
FPAP ORTHOMETRIC HEIGHT	+03121

QUALITY
16
CHECKED

CITY AND STATE TEKAMAH, NE	ELEVATION: 1027 AIRPORT NAME: TEKAMAH MUNI	TDZE: 1026 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 33, AMDT 1 30 MARCH 2017	SUP: RNAV (GPS) RWY 32
				AMDT: ORIG
				DATED: 10/25/2007