

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW36 CLIMB TO 3000 DIRECT CIGAY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 184.48 INBOUND. CHART FAS OBST: 203 CTRL TWR 302313N/0842113W. DISTANCE TO THLD FROM 200 HAT: 0.50 NM. CHART VDP AT 1.09 NM TO RW36* *LNAV ONLY. WAAS CHANNEL # 60900 REFERENCE PATH ID: W36A CHART CIRCLING ICON. CHART ASR LTP HAE: -10.6 M								
ATYIP (IAF)	HEMUX (NOPT) (TF) (FB) (RNP 1.00)	094.42 / 6.30	3000									
CEVIR (IAF)	HEMUX (NOPT) (TF) (FB) (RNP 1.00)	274.54 / 6.30	3000									
HEMUX (IF/IAF)	BUPYA (TF) (FB) (RNP 1.00)	004.48 / 6.10	1600									
BUPYA (FAF)	XIGIQ/2.50 NM TO RW36 (TF) (FB) (RNP 0.30)	004.48 / 2.21										
XIGIQ/2.50 NM TO RW36	RW36 (MAP) (TF) (FO) (RNP 0.30)	004.48 / 2.50										
(SEE FORM 8260-10) THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 17-25.												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S HEMUX, RT, 004.48 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 004.48 FAF: BUPYA DIST FAF TO MAP: 4.71 THLD: 4.71 4. MIN. ALT: HEMUX 3000, BUPYA 1600, XIGIQ/2.50 NM TO RW36 880* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1600 GS ALT AT: BUPYA 1600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS CLEAR 8. MSA FROM: _____				MAG VAR: 5W EPOCH YEAR: 2020								
MINIMUMS												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @						
CATEGORY ==>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA**	262	2400	200	262	2400	200	262	2400	200	262	2400	200
LNAV/VNAV DA	364	2400	302	364	2400	302	364	2400	302	364	2400	302
LNAV MDA	460	2400	398	460	2400	398	460	3500	398	460	3500	398
CIRCLING	580	1	497	600	1	517	640	1 1/2	557	780	2 1/4	697
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -7C (20F) OR ABOVE 54C (130F). @ CAT D 800-2 1/4 CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). *LNAV ONLY CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.												
CITY AND STATE		ELEVATION: 83 TDZE: 62		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
TALLAHASSEE, FL		AIRPORT NAME: TALLAHASSEE INTL				RNAV (GPS) RWY 36, AMDT 2A			AMDT: 2			
						7 DECEMBER 2017			DATED 05/26/2016			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW36 (MAP)	262 MSL (CA)	004.48	

262 MSL	CIGAY (DF) (FO) (RNP 1.00)	3000
---------	----------------------------	------

TAA

	FROM	TO	ALT
1.	274/30 CW 094/30 (NOPT)	HEMUX (IF/IAF) (FB)	3000
2.	094/30 CW 184/30	ATYIP (IAF) (FB)	3000
3.	184/30 CW 274/30	184/15 CW 274/15	3300
	184/15 CW 274/15	CEVIR (IAF) (FB)	3000

QUALITY
4
CHECKED

CITY AND STATE
TALLAHASSEE, FL

ELEVATION: 83 TDZE: 62
 AIRPORT NAME:
 TALLAHASSEE INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 36, AMDT 2A
 7 DECEMBER 2017

SUP:
 AMDT: 2
 DATED: 05/26/2016

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KTLH
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	302335.6525N
LTP/FTP LONGITUDE	0842131.6210W
LTP/FTP ELLIPSOIDAL HEIGHT	-00106
FPAP LATITUDE	302504.9585N
FPAP LONGITUDE	0842132.5565W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0616
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 6F2DB19A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00171
FPAP ORTHOMETRIC HEIGHT	+00171

QUALITY
4
CHECKED

CITY AND STATE TALLAHASSEE, FL	ELEVATION: 83 TDZE: 62 AIRPORT NAME: TALLAHASSEE INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 2A 7 DECEMBER 2017	SUP:
				AMDT: 2
				DATED: 05/26/2016