

**Federal Aviation
Administration**

Transmittal Letter 23-13

April 28, 2023

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
6/15/2023	NY	Canandaigua a	Canandaigua	3/0608	2/28/2023	RNAV (GPS) RWY 13, Amdt 2A

AIRAC Date: 15 JUNE 2023

FDC 3/0608 IUA IAP CANANDAIGUA, CANANDAIGUA, NY. RNAV (GPS) RWY 13, AMDT 2A... MSA RWY 13 25 NM MINIMUM ALTITUDE 3800. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: DME/DME RNP-0.3 NA. LPV VISIBILITY ALL CATS 3/4. LNAV/VNAV VISIBILITY ALL CATS 1 3/8. LNAV VISIBILITY CAT C 1. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROCHESTER ALTIMETER SETTING AND INCREASE LPV DA TO 1138 FEET AND ALL VISIBILITIES 1/4 SM. INCREASE LNAV/VNAV DA TO 1333 FEET AND ALL VISIBILITIES 1/8 SM. INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 3/8 SM, AND CIRCLING VISIBILITY CAT C 1/2 SM. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16 C OR ABOVE 54 C. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK IN PROFILE AT TUDDO AND VDP. THIS IS RNAV (GPS) RWY 13, AMDT 2B. 2302281452-PERM