

U.S. Department of Transportation
Federal Aviation Administration

**RNAV STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE								
PAWEJ WP (IAF)		ODYIY WP (NOPT) (TF) (FB)			074.42 / 5.00			3400		LNAV: RW16						
VOJIB WP (IAF)		ODYIY WP (NOPT) (TF) (FB)			254.53 / 5.00			3400		CLIMB TO 2000 DIRECT AGEGE WP AND HOLD.						
ODYIY WP (IF/IAF)		INNUP WP (TF) (FB)			164.47 / 7.04			2300								
RW16 (MAP)		AGEGE WP (DF) (FO)						2000								
										ADDITIONAL FLIGHT DATA:						
										HOLD S, RT, 345 INBOUND						
										FAS OBST: 607 TREE 334818/0934041						
1. PT <u>NA</u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)										FINAL SEGMENT (TF) INNUP WP TO RW16: 3.00 / 42 MAG VAR: 3E EPOCH YEAR: 2000						
2. HOLD N ODIYIY WP, RT, 164.47 INBOUND, 3400 FT IN-LIEU OF PT (IAF)																
3. FAC: <u>164.49</u> FAF: <u>INNUP WP</u> DIST FAF TO MAP: <u> </u> - THLD: <u>5.96</u>																
4. MIN. ALT: <u>ODYIY WP 3400, INNUP WP 2300</u>																
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>																
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>																
7. GS ANGLE: <u> </u> TCH: <u>34:1 IS CLEAR</u>																
8. MSA FROM: <u> </u>																
MINIMUMS																
TAKEOFF: <input checked="" type="checkbox"/> STANDARD				SEE FAA FORM 8260-15 FOR THIS AIRPORT				ALTERNATE: <input type="checkbox"/> N <input checked="" type="checkbox"/> A <input type="checkbox"/> X								
CATEGORY		A			B			C			D			E		
		DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA		920	1	561	920	1	561	920	1 1/2	561	920	1 3/4	561			
CIRCLING		920	1	561	920	1	561	920	1 1/2	561	920	2	561			
NOTES: USE TEXARKANA ALTIMETER SETTING																
GPS or RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA																
CITY AND STATE		ELEVATION: 359 TDZE: 359		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:						SUP:				
HOPE, AR		AIRPORT NAME: HOPE MUNI		RNAV		JUN 13 2002 RNAV(GPS) RWY 16, ORIG						AMDT: NONE				
												DATED				

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV **STANDARD INSTRUMENT APPROACH PROCEDURE**
FLIGHT STANDARDS SERVICE - FAR PART 9733

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA:

FROM	TO	ALTITUDE
1. 074/30 CW 255/30	ODYIY WP (IF/IAF)(NOPT)	3400
2. 255/30 CW 344/30	VOJIB WP (IAF)	3400
3. 344/30 CW 074/30	PAWEJ WP (IAF)	3400

CITY AND STATE

HOPE, AR

ELEVATION: 359 TDZE: 359
AIRPORT NAME:

HOPE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

JUN 13 2002

RNAV (GPS) RWY 16, ORIG

SUP:

AMDT: NONE

DATED: