

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW14 CLIMB TO 2000 DIRECT TO POMDE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 319.80 INBOUND. CHART FAS OBST: 244 TOWER 294853N/0945816W WADOB TO RW14: 3.04/40.
YEBUK (IAF)	JAVIG (FB)	229.74 / 5.00	1700	
VINXE (IAF)	JAVIG (FB)	049.66 / 5.00	1700	
JAVIG (IF)	WADOB (FB)	139.70 / 5.00	1400	

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT JAVIG
3. FAC: 139.73 FAF: WADOB DIST FAF TO MAP: 4.12 THLD: 4.12
4. MIN. ALT: JAVIG 1700, WADOB 1400
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW14 3100

MAG VAR: 3E EPOCH YEAR: 2010

MINIMUMS

TAKEOFF:	<input type="checkbox"/>	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input checked="" type="checkbox"/>										
CATEGORY =====>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	500	1	468	500	1	468		NA			NA					
CIRCLING	500	1	466	500	1	466		NA			NA					

NOTES:
CHART NOTE: CIRCLING NA AT NIGHT.
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PLANVIEW NOTE: RADAR REQUIRED
SEE 8260-10

CITY AND STATE	ELEVATION: 34 TDZE: 32	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
BAYTOWN, TX	AIRPORT NAME:	RNAV	RNAV (GPS) RWY 14, ORIG	AMDT: NONE
	BAYTOWN		29 JUL 2010	DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART PROFILE NOTE: VGSi AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE WILLIAM P HOBBY
ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.

CITY AND STATE

BAYTOWN, TX

ELEVATION: 34 TDZE: 32

AIRPORT NAME:

BAYTOWN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 14, ORIG

29 JUL 2010 -

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
CHECKED

CITY AND STATE BAYTOWN, TX	ELEVATION: 34 TDZE: 32 AIRPORT NAME: BAYTOWN	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 14, ORIG 29 JUL 2010	SUP:
				AMDT: NONE
				DATED: