

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM	TO	COURSE AND DISTANCE				ALTITUDE	MAP: INL VORTAC CLIMB TO 2900 THEN RIGHT TURN DIRECT INL VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 134.00 INBOUND. CHART FAS OBST: 1512 TOWER 483725N/0933220W CHART VDP AT 2.52 DME; DISTANCE VDP TO THLD 2.02 MILES. CHART TDZE 1184. FAC CROSSES RWY C/L EXTENDED 5018 FROM THLD.										
1. PT <u> L </u> SIDE OF COURSE <u> 314.00 </u> OUTBOUND <u> 2900 </u> FT WITHIN <u> 10 </u> MILES OF <u> INL VORTAC </u> (IAF) 2. <u> </u> 3. FAC <u> 134.00 </u> FAF <u> </u> DIST FAF TO MAP <u> </u> THLD <u> </u> 4. MIN. ALT <u> </u> 8. MSA FROM: <u> INL VORTAC 3200 </u>														MAG VAR: 6E		EPOCH YEAR: 1965	
MINIMUMS																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: NA		STANDARD @					
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-13	1880	1/2	696	1880	1/2	696	1880	1 1/2	696	1880	1 3/4	696					
CIRCLING	1880	1	695	1880	1	695	1880	2	695	1880	2 1/4	695					
NOTES: CHART NOTE: CIRCLING TO RWY 4-22 NA AT NIGHT. CHART NOTE: VDP NA WHEN USING BAUDETTE ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BAUDETTE ALTIMETER SETTING AND INCREASE ALL MDAS 140 FEET, AND S-13 CATS A/B VISIBILITY 1/4 MILE, CATS C/D VISIBILITY 1/2 MILE. INCREASE SEE 8260-10																	
CITY AND STATE INTERNATIONAL FALLS, MN		ELEVATION: 1185 TDZE: 1184 AIRPORT NAME: FALLS INTL		FACILITY IDENTIFIER: INL		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 13, AMDT 14 APR 10 2008						SUP VOR OR GPS RWY					
												13					
												AMDT 13A					
												DATE 09/07/2000					

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CIRCLING CAT B VISIBILITY 1/4 MILE, CAT C AND D 1/2 MILE. FOR INOPERATIVE MALSR WHEN USING BAUDETTE ALTIMETER SETTING, INCREASE S-13 CAT A VISIBILITY 1/4 MILE.

CITY AND STATE

INTERNATIONAL FALLS, MN

ELEVATION: 1185 TDZE: 1184

AIRPORT NAME:

FALLS INTL

FACILITY
IDENTIFIER:

INL

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 13, AMDT 14

APR 10 2008

SUP: VOR OR GPS RWY
13

AMDT: 13A

DATED: 09/07/2000