

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ICREB (IAF)	IZZIE (NOPT) (FB)	356.82 / 5.00	3000	LNAV/VNAV: DA LNAV: RW26 CLIMB TO 3000 DIRECT EVOCO AND ON TRACK 226.80 TO COLMI AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 356.50 INBOUND. CHART FAS OBST: 976 TREE 402915N/0843233W DISTANCE TO THLD FROM 384 HAT: 1.03 NM. CHART: WAPAKONETA AWOS-3
LUSHU (IAF)	IZZIE (NOPT) (FB)	176.80 / 5.00	3000	
IZZIE (IF/IAF)	EVOZU (FB)	266.81 / 6.01	2600	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD **E** IZZIE, RT, 266.81 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 266.73 FAF: EVOZU DIST FAF TO MAP: 4.86 THLD: 4.86
- MIN. ALT: **IZZIE 3000, EVOZU 2600**
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2600 GS ALT AT: EVOZU 2600 OM: MM: IM:
- GS ANGLE: 3.20 TCH: 40.0
- MSA FROM:

MAG VAR: 4W

EPOCH YEAR: 1995

MINIMUMS

TAKEOFF: <u> </u>	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input checked="" type="checkbox"/> X										
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV/VNAV DA	1277	1 1/4	384	1277	1 1/4	384	1277	1 1/4	384		NA				
LNAV MDA	1260	1	367	1260	1	367	1260	1	367		NA				
CIRCLING	1320	1	426	1360	1	466	1360	1 1/2	466		NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGSi AND RNAV GLIDEPATH NOT COINCIDENT.
 CHART NOTE: BARO-VNAV NA.
 SEE 8260-10

CITY AND STATE CELINA, OH	ELEVATION: 894 TDZE: 893 AIRPORT NAME: LAKEFIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 26, ORIG 11 FEB 2010	SUP: AMDT: NONE DATED
-------------------------------------	---	-------------------------------------	--	------------------------------------

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: USE WAPAKONETA ALTIMETER SETTING. WHEN NOT RECEIVED, USE JAMES M. COX DAYTON INTL ALTIMETER SETTING AND INCREASE ALL DA 73 FEET AND ALL MDA 80 FEET AND INCREASE LNAV/VNAV CATS A/B/C AND LNAV CAT C VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	177/30 CW 357/30 (NOPT)	IZZIE (IF/AF) (FB)	3000
2.	357/30 CW 087/30	ICREB (IAF) (FB)	3000
3.	087/30 CW 177/30	LUSHU (IAF) (FB)	3000

CITY AND STATE

CELINA, OH

ELEVATION: 894 TDZE: 893

AIRPORT NAME:

LAKEFIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 26, ORIG

11 FEB 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

PAGE 3 OF 3 PAGES