

<b>RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
<b>TERMINAL ROUTES</b>								<b>MISSED APPROACH</b>							
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LNAV: RW35  CLIMB TO 1700 DIRECT RAYCI AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD NE, RT, 218.98 INBOUND. CHART FAS OBST: 253 ELECTRICAL SYSTEM 293417N/0951640W NAPS TO RW35: 3.05/41.							
OHGOK (IF)		NAPSY (FB)		355.94 / 5.00		2000									
NAPSY (FAF)		RW35 (MAP) (FO)		355.94 / 5.92											
RW35 (MAP)		446 MSL		355.94											
446 MSL		RAYCI (FO)				1700									
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF)															
2. PROFILE STARTS AT OHGOK															
3. FAC: <u>355.94</u> FAF: <u>NAPSY</u> DIST FAF TO MAP: <u>5.92</u> THLD: <u>5.92</u>															
4. MIN. ALT: <u>OHGOK 3000, NAPS 2000</u>															
5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u>															
6. MIN GS INCPT: <u>      </u> GS ALT AT: <u>      </u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u>															
7. GS ANGLE: <u>      </u> TCH: <u>34:1</u> IS NOT CLEAR															
8. MSA FROM: <u>RW35 3100</u>								MAG VAR: 3E EPOCH YEAR: 2015							
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		STANDARD							
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	560	1	514	560	1	514	560	1 1/2	514	560	1 3/4	514			
CIRCLING	560	1	514	560	1	514	560	1 1/2	514	600	2	554			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: RADAR REQUIRED. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: NIGHT LANDING: RWY 35 NA.															
CITY AND STATE				ELEVATION: 46 TDZE: 46		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
HOUSTON, TX				AIRPORT NAME:				RNAV (GPS) RWY 35, AMDT 1A				AMDT: 1			
				WILLIAM P HOBBY				29 MAY 2014				DATED 11/01/2001			

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KHOUK4FR35	R	010	OHGOKK4EA0E	I	IF				+ 03000	18000			B JS
SUSAP KHOUK4FR35	R	020	NAPSYK4EA1E	F	051TF		35590050		+ 02000		RW35	K4PGB	JS
SUSAP KHOUK4FR35	R	020	NAPSYK4EA2WN			N	ALNAV						JS
SUSAP KHOUK4FR35	R	030	RW35 K4PGOGY	M	031TF		35590059		00084		-305		B JS
SUSAP KHOUK4FR35	R	040		0	M	CA	3559		+ 00446				B JS
SUSAP KHOUK4FR35	R	050	RAYCIK4EA0EY		DF				+ 01700				B JS
SUSAP KHOUK4FR35	R	060	RAYCIK4EA0EE	R	HM		21900040		+ 01700				B JS

[illegible][illegible]

CITY AND STATE <b>HOUSTON, TX</b>	ELEVATION: <b>46</b>	TDZE: <b>46</b>	FACILITY IDENTIFIER:  <b>RNAV</b>	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: <b>WILLIAM P HOBBY</b>			<b>RNAV (GPS) RWY 35, AMDT 1A</b>	AMDT: <b>1</b>
				<b>29 MAY 2014</b>	DATED: <b>11/01/2001</b>

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		OHGOK	010	FACF	IF		FB				AA 03000	
		NAPSY	020	FAF	TF		FB	0.5	355.9 (358.9T)	005.0	AA 02000	
		RW35	030	MAP	TF		FO	0.3	355.9 (358.9T)	005.9	AT 00084	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		355.9 (358.9T)		AA 00446	
	RAYCI	050		DF		FO				AA 01700	
	RAYCI	060		HM	R	FO		219.0 (222.0T)	004.0	AA 01700	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	NAPSY	N293213.40	W0951656.01	N2932.223	W09516.934
	OHGOK	N292712.41	W0951649.66	N2927.207	W09516.828
	RAYCI	N294953.66	W0950419.69	N2949.894	W09504.328
	RW35	N293809.12	W0951703.54	N2938.152	W09517.059

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00043	41

CITY AND STATE  
HOUSTON, TX

ELEVATION: 46 TDZE: 46  
 AIRPORT NAME:  
 WILLIAM P HOBBY

FACILITY  
IDENTIFIER:  
 RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  
 RNAV (GPS) RWY 35, AMDT 1A  
 29 MAY 2014

SUP:	
AMDT:	1
DATED:	11/01/2001