

**Federal Aviation  
Administration**

**Transmittal Letter 20-19**

**July 24, 2020**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/10/2020	GA	Savannah	Savannah/Hilton Head Intl	0/7573	7/9/2020	RNAV (GPS) RWY 10, Amdt 2A

**AIRAC Date: 10 SEPTEMBER 2020**

FDC 0/7573 SAV IAP SAVANNAH/HILTON HEAD INTL, SAVANNAH, GA. RNAV (GPS) RWY 10, AMDT 2A... CIRCLING MDA 740/HAA 690 CATS C AND D. VIS CAT C 2, CAT D 2-1/4. CHART CIRCLING ICON. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HILTON HEAD ISLAND ALTIMETER SETTING AND INCREASE ALL DA 65 FEET AND ALL MDA 80 FEET; INCREASE LNAV/VNAV ALL CATS AND CIRCLING CATS C/D VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 10, AMDT 2B. 2007091318-PERM