

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KGLH	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 18R	<u>ORIGINAL/AMENDMENT</u> 1	<u>CITY</u> GREENVILLE	<u>STATE</u> MS		
<u>AIRPORT ELEVATION</u> 131	<u>TDZE</u> 128	<u>SUPERSEDED</u> RNAV (GPS) RWY 18R	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>DATED</u> 06/17/2021	<u>MAG VAR</u> 1W	<u>EPOCH YEAR</u> 2025
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 25 JANUARY 2024	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TAA

FROM	FIX TYPE	TO	FIX TYPE	ALTITUDE
1. 091/30 CW 271/30	NOPT	091/5 CW 271/5		2100
2. 091/5 CW 271/5		EZOMY	IF/IAF	2000
3. 271/30 CW 001/30		271/5 CW 001/5		3200
4. 271/5 CW 001/5		YAGUT	IAF	2000
5. 001/30 CW 091/30		WEXOG	IAF	2000

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
YAGUT	IAF	EZOMY	NOPT	TF	FB	1.00	271.06	6.00	2000
WEXOG	IAF	EZOMY	NOPT	TF	FB	1.00	090.92	6.00	2000
EZOMY	IF/IAF	AJEHO		TF	FB	1.00	180.99	6.03	1800
AJEHO	FAF	RW18R	MAP	TF	FO	0.30	180.99	5.09	
RW18R	MAP	328 MSL		CA			180.99		
328 MSL		KEVNE		DF	FO	1.00			2000

QUALITY
10
CHECKED

MISSED APPROACH**MAP:**

LPV: DA

LNAV/VNAV: DA

LNAV: RW18R

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 2000 DIRECT KEVNE AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:**PROFILE:**

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2. HOLD N EZOMY, RT, 180.99 INBOUND, 2000 FT. IN LIEU OF PT (IAF), MAX 6000.					
3. FAC:	180.99	FAF: AJEHO	DIST FAF TO MAP: 5.09		DIST FAF TO THLD: 5.09
4. MIN ALT:	EZOMY 2000, AJEHO 1800				
5. DIST TO THLD FROM OM:	MM:	IM:	150 HAT:	200 HAT: 0.47	GS ANT:
6. MIN GP INCPT:	1800	GP ALT AT PFAF :	AJEHO 1800	OM:	MM:
7. GP ANGLE:	3.00	34:1: IS CLEAR	20:1: IS CLEAR	TCH: 50.0	IM:
8. MSA FROM:					

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -7°C OR ABOVE 54°C.

ADDITIONAL FLIGHT DATA:

HOLD S, RT, 000.99 INBOUND.

FAS OBST: 330 AAO 333334N/0905903W.

335 AAO 333410N/0905930W.

CHART VDP AT 1.25 NM TO RW18R.

WAAS CHANNEL # 70411

REFERENCE PATH ID: W18B

CHART CIRCLING ICON.

LTP HAE: 12.4 M



MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE.

<u>CATEGORY:</u>	<u>A</u>			<u>B</u>			<u>C</u>			<u>D</u>			<u>E</u>		
<u>FINAL TYPE</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>VIS</u>	<u>HAT/HAA</u>
LPV DA	328	1	200	328	1	200	328	1	200	328	1	200			
LNAV/VNAV DA	523	1 1/8	395	523	1 1/8	395	523	1 1/8	395	523	1 1/8	395			
LNAV MDA	580	1	452	580	1	452	580	1 3/8	452	580	1 3/8	452			
CIRCLING	600	1	469	600	1	469	600	1 1/2	469	800	2	669			



FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KGLH
RUNWAY	RW18R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18B
LTP/FTP LATITUDE	332939.0260N
LTP/FTP LONGITUDE	0905913.9980W
LTP/FTP ELLIPSOIDAL HEIGHT	+00124
FPAP LATITUDE	332809.7600N
FPAP LONGITUDE	0905913.9680W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0608
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
CRC REMAINDER	0BF28FBE

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00391
FPAP ORTHOMETRIC HEIGHT	+00391

QUALITY
10
CHECKED