U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

LOC/DME

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
EMQIF INT (IAF)	IZLAR / IMT 11.00 DME	100.00/4.94(HDG)&189.67/4.16 (I-IMT)	3400
IZLAR	NOODL / IMT 6.00 DME	189.67 / 5.00 (I-IMT)	2900

MISSED APPROACH

MAP: IMT 1.48 DME

CLIMB TO 3100 DIRECT KORDS LOM AND HOLD; OR WHEN DIRECTED BY ATC, CLIMB TO 3100 THEN LEFT TURN DIRECT IMT VORTAC AND HOLD N, RT, 190.53 INBOUND.

ADDITIONAL FLIGHT DATA:

HOLD S, RT, 010.37 INBOUND
FAS OBST: 1399 TREE 455306 / 880600
NOODL TO RWY 19: 2.99 / 45

1. PT NA SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. PROFILE STARTS AT IZLAR
3. FAC 189.67 FAF NOODL DIST FAF TO MAP - THLD 5.27
4. MIN. ALT IZLAR 3400, NOODL 2900
8. MSA FROM: IMT VORTAC 230 - 330 3300, 330 - 230 2900

MAG VAR: 2W EPOCH YEAR: 85

MINIMUMS

TAKEOFF: | | STANDARD | X | SEE FAA FORM 8260-15 FOR THIS AIRPORT | ALTERNATE: N A | | STANDARD

CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA
S-19	1660	1	478	1660	1	478	1660	1 1/4	478	1660	1 1/2	478			
CIRCLING	1660	1	478	1720	1	538	1780	1 1/2	598	1780	2	598			

NOTES:

CIRCLING NOT AUTHORIZED NE OF RWYS 19 AND 31.
DISREGARD GLIDESLOPE INDICATIONS.
DME FROM IMT VORTAC.
SIMULTANEOUS RECEPTION OF I-IMT AND IMT DME REQUIRED.
ADF REQUIRED.

CITY AND STATE	ELEVATION: 1182 TDZE: 1182 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP
			10 AUG 00	AMDT 12
IRON MOUNTAIN/KINGSFORD, MI	FORD	I-IMT	LOC/DME BC RWY 19, AMDT 13	DATED 9/13/98