

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW18 CLIMB TO 1300 THEN CLIMBING RIGHT TURN TO 2200 DIRECT EPICU AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 619 AAO 320143N/0850719W CHART FAS OBST: 459 TREE 315824N/0850804W CHART 657 TOWER 320230N/0850759W DISTANCE TO THLD FROM 314 HATH: 0.86 NM. WAAS CHANNEL # 86723 REFERENCE PATH ID: W18A CHART EUFAULA NATIONAL WILDLIFE REFUGE LTP HAE: 59.9 M											
EPICU (IF/IAF)	CASDO (FB)	187.63 / 6.95	2000												
CASDO (FAF)	RW18 (MAP) (FO)	187.62 / 5.27													
RW18 (MAP)	1300 MSL	187.62	1300												
1300 MSL	EPICU (FO)		2200												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)				MAG VAR: 4W EPOCH YEAR: 2010											
2. HOLD N EPICU, RT, 187.63 INBOUND, 2200 FT. IN LIEU OF PT (IAF)															
3. FAC: 187.62 FAF: CASDO DIST FAF TO MAP: 5.27 THLD: 5.27															
4. MIN. ALT: EPICU 2200, CASDO 2000															
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:															
6. MIN GS INCPT: 2000 GS ALT AT: CASDO 2000 OM: MM: IM:															
7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR															
8. MSA FROM:															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	597	1	314	597	1	314	597	1	314	597	1	314			
LNAV/VNAV DA	704	1 1/2	421	704	1 1/2	421	704	1 1/2	421	704	1 1/2	421			
LNAV MDA	940	1	657	940	1	657	940	1 7/8	657	940	1 7/8	657			
CIRCLING	940	1	655	940	1	655	940	1 7/8	655	1000	2 1/4	715			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGS1 AND RNAV GLIDEPATH NOT COINCIDENT. CHART NOTE: BARO-VNAV NA. CHART NOTE: USE CLAYTON ALTIMETER SETTING; WHEN NOT RECEIVED, USE COLOMBUS, GA ALTIMETER SETTING (SEE FORM 8260-10)															
CITY AND STATE EUFAULA, AL				ELEVATION: 285 THRE: 283 AIRPORT NAME: WEEDON FIELD		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1 25 AUG 2011				SUP: AMDT: ORIG DATED 12/20/2007			

QUALITY
 2
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

AND INCREASE ALL DA 33 FEET AND ALL MDA 40 FEET; INCREASE LPV ALL CATS AND LNAV CATS C AND D AND CIRCLING CAT C VISIBILITY 1/8 MILE, AND CIRCLING D VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	098/30 CW 278/30 (NOPT)	098/10 CW 278/10	3300
2.	098/10 CW 278/10	EPICU (IF/AF) (FB)	2200
3.	278/30 CW 098/30	278/15 CW 098/15	2600
4.	278/15 CW 098/15	EPICU (IF/AF) (FO)	2200

QUALITY
2
CHECKED

CITY AND STATE

EUFAULA, AL

ELEVATION: 285

THRE: 283

AIRPORT NAME:

WEEDON FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, AMDT 1

25 AUG 2011

SUP:

AMDT: ORIG

DATED: 12/20/2007

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KEUF
RUNWAY RW18
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W18A
LTP/FTP LATITUDE 315729.4375N
LTP/FTP LONGITUDE 0850742.3095W
LTP/FTP ELLIPSOIDAL HEIGHT +00599
FPAP LATITUDE 315600.3300N
FPAP LONGITUDE 0850748.9200W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1224
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

FCCE9C15

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K7
LTP ORTHOMETRIC HEIGHT +00863
FPAP ORTHOMETRIC HEIGHT +00863

QUALITY
2
CHECKED

CITY AND STATE EUFAULA, AL	ELEVATION: 285 THRE: 283 AIRPORT NAME: WEEDON FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1 25 AUG 2011	SUP:
				AMDT: ORIG
				DATED: 12/20/2007

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
6
CHECKED

CITY AND STATE EUFULA, AL	ELEVATION: 285 THRE: 283	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, AMDT 1 25 AUG 2011	SUP:
	AIRPORT NAME:			AMDT: ORIG
	WEEDON FIELD			DATED: 12/20/2007