

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES				MISSED APPROACH											
FROM OGVIE (IF/IAF) SOYOT (FAF) YEMQA/2.00 NM TO RW20 RW20 (MAP) 550 MSL	TO SOYOT (FB) YEMQA/2.00 NM TO RW20 (FB) RW20 (MAP) (FO) 550 MSL COSAD (FO)	COURSE AND DISTANCE 197.91 / 6.10 197.89 / 3.03 197.89 / 2.00 197.89	ALTITUDE 1900 2500	LPV: DA LNAV/VNAV: DA LNAV: RW20 CLIMB TO 2500 DIRECT COSAD AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, LT, 017.82 INBOUND. CHART FAS OBST: 354 TREE 361413N/0900150W DISTANCE TO THLD FROM 292 HATH: 0.79 NM. CHART VDP AT 1.01 MILES TO RW20* *LNAV ONLY. WAAS CHANNEL # 42635 REFERENCE PATH ID: W20A CHART CIRCLING ICON. LTP HAE: 50.3 M											
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD N OGVIE, RT, 197.91 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC: <u>197.89</u> FAF: <u>SOYOT</u> DIST FAF TO MAP: <u>5.03</u> THLD: <u>5.03</u> 4. MIN. ALT: <u>OGVIE 2500, SOYOT 1900, YEMQA/2.00 NM TO RW20 920*</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>1900</u> GS ALT AT: <u>SOYOT 1900</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS NOT CLEAR 8. MSA FROM: <u> </u>				MAG VAR: 0E EPOCH YEAR: 2000											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	550	1	292	550	1	292	550	1	292	550	1	292			
LNAV/VNAV DA	598	1 1/8	340	598	1 1/8	340	598	1 1/8	340	598	1 1/8	340			
LNAV MDA	620	1	362	620	1	362	620	1	362	620	1	362			
CIRCLING	660	1	398	720	1	458	720	1 1/2	458	900	2	638			

NOTES:
 CHART NOTE: CIRCLING TO RWY 18/36 NA AT NIGHT.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F).
 CHART NOTE: CIRCLING NA WEST OF RWYS 2 AND 18.
 CHART NOTE: DME/DME RNP-0.3 NA.
 (SEE FORM 8260-10)

CITY AND STATE KENNETT, MO	ELEVATION: 262 THRE: 258 AIRPORT NAME: KENNETT MEMORIAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1 6 MARCH 2014	SUP: AMDT: ORIG DATED 04/13/2006
-------------------------------	---	------------------------------	---	--

QUALITY
 9
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE BLYTHEVILLE MUNI ALTIMETER SETTING AND INCREASE ALL DA 47 FEET AND ALL MDA 60 FEET; INCREASE LPV VISIBILITY 1/8 MILE ALL CATS; INCREASE LNAV/VNAV VISIBILITY 1/4 MILE ALL CATS; INCREASE LNAV CAT C/D AND CIRCLING CAT D VISIBILITY 1/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART NOTE: VDP AND BARO-VNAV NA WHEN USING BLYTHEVILLE MUNI ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	108/30 CW 288/30 (NOPT)	OGVIE (IF/IAF) (FB)	2500
2.	288/30 CW 108/30	OGVIE (IF/IAF) (FO)	2500

QUALITY
9
CHECKED

CITY AND STATE
KENNETT, MO

ELEVATION: 262 THRE: 258
AIRPORT NAME:
KENNETT MEMORIAL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 20, AMDT 1
6 MARCH 2014

SUP:
AMDT: ORIG
DATED: 04/13/2006

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KTKX
RUNWAY RW20
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W20A
LTP/FTP LATITUDE 361349.0265N
LTP/FTP LONGITUDE 0900207.3150W
LTP/FTP ELLIPSOIDAL HEIGHT +00503
FPAP LATITUDE 361224.1100N
FPAP LONGITUDE 0900241.1000W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1224
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

784ACEF3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K3
LTP ORTHOMETRIC HEIGHT +00787
FPAP ORTHOMETRIC HEIGHT +00787

QUALITY
9
CHECKED

CITY AND STATE

KENNETT, MO

ELEVATION: 262

THRE: 258

AIRPORT NAME:

KENNETT MEMORIAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 20, AMDT 1

6 MARCH 2014

SUP:

AMDT: ORIG

DATED: 04/13/2006

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KTKXK3FR20	AOGVIE	010OGVIEK3EA0EE	AR	HF		19790040	+	02500	18000		A	JS
SUSAP	KTKXK3FR20	R	010OGVIEK3EA0E	I	IF			+	02500	18000		A	JS
SUSAP	KTKXK3FR20	R	020SOYOTK3EA1E	F	051TF		19790061	+	01900			A	JS
SUSAP	KTKXK3FR20	R	020SOYOTK3EA2WALPV			ALNAV/VNAV							JS
SUSAP	KTKXK3FR20	R	021YEMQAK3EA0E	S	031TF		19790030	V	0092000935		-300	A	JS
SUSAP	KTKXK3FR20	R	030RW20	K3PGOGY	M	031TF	19790020		00298		-300	A	JS
SUSAP	KTKXK3FR20	R	040		0	M	CA	1979	+	00550		A	JS
SUSAP	KTKXK3FR20	R	050COSADK3EA0EY		DF			+	02500			A	JS
SUSAP	KTKXK3FR20	R	060COSADK3EA0EE	L	HM		01780040	+	02500			A	JS

[illegible][illegible]

QUALITY
9
CHECKED

CITY AND STATE KENNETT, MO	ELEVATION: 262 THRE: 258	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1	SUP:
	AIRPORT NAME: KENNETT MEMORIAL	RNAV	6 MARCH 2014	AMDT: ORIG
				DATED: 04/13/2006

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	OGVIE	OGVIE	010	IAF	HF	R	FO		197.9(197.9T)	004.0	AA 02500	
		OGVIE	010	FACF	IF		FB				AA 02500	
		SOYOT	020	FAF	TF		FB	0.5	197.9(197.9T)	006.1	AA 01900	
		YEMQA	021	SDF	TF		FB	0.3	197.9(197.9T)	003.0	AA 00920	GS 00935
		RW20	030	MAP	TF		FO	0.3	197.9(197.9T)	002.0	AT 00298	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		197.9(197.9T)		AA 00550	
	COSAD	050		DF		FO				AA 02500	
	COSAD	060		HM	L	FO		017.8(017.8T)	004.0	AA 02500	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	COSAD	N360225.37	W0900638.58	N3602.423	W09006.643
	OGVIE	N362425.43	W0895753.46	N3624.424	W08957.891
	SOYOT	N361836.64	W0900012.74	N3618.611	W09000.212
	YEMQA	N361543.40	W0900121.79	N3615.723	W09001.363
	RW20	N361349.03	W0900207.32	N3613.817	W09002.122

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW20	00258	40

QUALITY
9
CHECKED

CITY AND STATE KENNETT, MO	ELEVATION: 262	THRE: 258	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: KENNETT MEMORIAL		RNAV	RNAV (GPS) RWY 20, AMDT 1	AMDT: ORIG
				6 MARCH 2014	DATED: 04/13/2006