

**Federal Aviation
Administration**

Transmittal Letter 21-11

April 2, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/20/2021	IN	Goshen	Goshen Muni	1/0942	3/11/2021	RNAV (GPS) RWY 27, Orig-A

AIRAC Date: 20 MAY 2021

FDC 1/0942 GSH IAP GOSHEN MUNI, GOSHEN, IN. RNAV (GPS) RWY 27, ORIG-A...
CIRCLING CAT B MDA 1320/HAA 493, CIRCLING CAT C MDA 1500/HAA 673, CIRCLING CAT
D MDA 1540/HAA 713, VIS CAT C 2, VIS CAT D 2 1/4. CHANGE NOTE TO READ: WHEN
LOCAL ALTIMETER SETTING NOT RECEIVED, USE WARSAW ALTIMETER SETTING:
INCREASE LPV DA TO 1160 FEET, LNAV/VNAV DA TO 1347 FEET, AND ALL MDAS 40 FEET;
INCREASE LPV VISIBILITY ALL CATS 1/8 SM, LNAV VISIBILITY CATS C/D 1/8 SM AND
CIRCLING VISIBILITY CAT D 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D
800-2 1/4 - NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 27,
ORIG-B. 2103041450-PERM