

**Federal Aviation
Administration**

Transmittal Letter 21-10

March 19, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/22/2021	TX	Longview	East Texas Rgnl	1/8118	3/3/2021	RNAV (GPS) RWY 13, Amdt 1B

22 APRIL 2021

FDC 1/8118 GGG IAP EAST TEXAS RGNL, LONGVIEW, TX. RNAV (GPS) RWY 13, AMDT 1B... CIRCLING CAT C MDA 980/HAA 614, CAT D MDA 1080/HAA 714, VISIBILITY CAT C 1 3/4 AND CAT D 2 1/4. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, CAT E 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE GILMER ALTIMETER SETTING AND INCREASE LPV DA TO 671 FEET; INCREASE LNAV/VNAV DA TO 785 FEET, AND VISIBILITY TO RVR 4500; INCREASE ALL MDA 60 FEET, AND LNAV CATS C/D VISIBILITY TO RVR 5000, AND CIRCLING CATS C/D/E VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 13, AMDT 1C. 2102251512-PERM