

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW06							
HUSKY		JUPEP (FO)		266.06 / 27.57				3000		CLIMB TO 3000 DIRECT HAMPP AND ON TRACK 121.72 TO HUSKY AND HOLD.							
TIROE (IAF)		JUPEP (NOPT) (FB)		099.42 / 17.30				3000									
BOWLN (IAF)		JUPEP (NOPT) (FB)		334.71 / 13.80				3000									
JUPEP (IF/IAF)		BGGOH (FB)		057.32 / 6.46				2500									
BGGOH (FAF)		ZUXUD/1.60 NM TO RW06 (FB)		057.40 / 3.44													
ZUXUD/1.60 NM TO RW06 (SEE FORM 8260-10)		RW06 (MAP) (FO)		057.40 / 1.60						ADDITIONAL FLIGHT DATA: HOLD SE, RT, 311.03 INBOUND. CHART FAS OBST: 1039 TREE 332301N/0842141W BGGOH TO RW06: 3.00/44. CHART CIRCLING ICON.							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																	
2. HOLD SW JUPEP, RT, 057.32 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																	
3. FAC: 057.40 FAF: BGGOH DIST FAF TO MAP: 5.04 THLD: 5.04																	
4. MIN. ALT: JUPEP 3000, BGGOH 2500, ZUXUD/1.60 NM TO RW06 1400																	
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																	
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																	
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																	
8. MSA FROM: RW06 3500																	
MAG VAR: 3W EPOCH YEAR: 1995																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X							
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LNAV MDA	1300	1	439	1300	1	439	1300	1 1/4	439	1300	1 1/4	439					
CIRCLING	1380	1	498	1380	1	498	1700	2 1/2	818	1740	2 3/4	858					
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HARTSFIELD-JACKSON ATLANTA INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET; INCREASE LNAV CATS C/D VISIBILITY 1/8 MILE AND CIRCLING CAT D VISIBILITY 1/4 MILE. (CONTINUED ON PAGE 2)																	
CITY AND STATE HAMPTON, GA		ELEVATION: 882 TDZE: 861 AIRPORT NAME: HENRY COUNTY AIRPORT				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 6, AMDT 2 15 SEPTEMBER 2016						SUP: AMDT: 1B DATED 05/29/2014			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW06 (MAP)	1282 MSL	057.40	
1282 MSL	HAMPP (FB)		
HAMPP	HUSKY (FO)	121.72 / 14.58	3000

NOTES, (CONT.):

CHART NOTE: NIGHT LANDING: RWY 6 NA.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT BOWLN ON V97 SOUTHBOUND.

QUALITY
23
CHECKED

CITY AND STATE

HAMPTON, GA

ELEVATION: 882

TDZE: 861

AIRPORT NAME:

HENRY COUNTY AIRPORT

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 6, AMDT 2
15 SEPTEMBER 2016

SUP:

AMDT: **1B**

DATED: **05/29/2014**

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - KHMP

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
BOWLN	010	BOWLN	IF	FB										E A
BOWLN	020	JUPEP	TF	FB	1.0	334.7						AA 03000		EE B
HUSKY	010	HUSKY	IF	FB										E
HUSKY	020	JUPEP	TF	FO	2.0	266.1						AA 03000		EY
HUSKY	030	JUPEP	HF	FO		057.3			R			AA 03000		EE A
TIROE	010	TIROE	IF	FB										E A
TIROE	020	JUPEP	TF	FB	1.0	099.4						AA 03000		EE B
	010	JUPEP	IF	FB								AA 03000		E I
	020	BGGOH	TF	FB	1.0	057.3				RW06		AA 02500		E F
	021	ZUXUD	TF	FB	0.3	057.4		3.00				AA 01400 GS 01406		E S
	030	RW06	TF	FO	0.3	057.4		3.00				AT 00896		GY M
	040		CA	FB		057.4						AA 01282		M
	050	HAMPP	DF	FB										E
	060	HUSKY	TF	FO	1.0	121.7						AA 03000		EY
	070	HUSKY	HM	FO		311.0			R			AA 03000		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
BOWLN	N330414.87	W0842339.36
HUSKY	N331949.65	W0835848.75
TIROE	N331823.23	W0845157.71
BGGOH	N332011.65	W0842511.55
HAMPP	N332651.71	W0841404.37
JUPEP	N331625.19	W0843127.55
ZUXUD	N332211.89	W0842151.36

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW06	N332307.83	W0842018.11	00852	44.0

QUALITY
23
CHECKED

CITY AND STATE HAMPTON, GA	ELEVATION: 882 TDZE: 861	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 6, AMDT 2 15 SEPTEMBER 2016	SUP:
	AIRPORT NAME: HENRY COUNTY AIRPORT			AMDT: 1B
				DATED: 05/29/2014