

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29									Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES													MISSED APPROACH								
FROM			TO			COURSE AND DISTANCE			ALTITUDE			ILS: DA LOC: 3.52 NM AFTER CABLE OM									
BSV VOR/DME (IAF)			BULIT INT			335.49 / 1.65			3000			CLIMB TO 1900 THEN CLIMBING RIGHT TURN TO 3000 DIRECT ACO VOR/DME AND HOLD. ALTERNATE MA (DO NOT CHART): CLIMB TO 1900 THEN CLIMBING LEFT TURN TO 3000 ON HEADING 230.00 AND BSV VOR/DME R-322 TO KEATN/BSV 15.31 DME AND HOLD (DME REQUIRED). ADDITIONAL FLIGHT DATA: HOLD E, RT, 272.00 INBOUND. CHART ARRIVAL HOLDING AT BSV VOR/DME: HOLD SE, RT, 335.00 INBOUND, 3000. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD SE KEATN/BSV 15.31 DME, LT, 322.41 INBOUND. CHART FAS OBST: 1331 TREES 405314N/0812649W. CHART 1377 TOWER 405049N/0812622W. CHART: ASR. CHART IN PLANVIEW: KEATN/BSV 15.31 DME. CHART PLANVIEW NOTE: RADAR REQUIRED.									
BULIT INT (IF)			CABLE OM			009.47 / 5.02 (I-CAK)			2400												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)													MAG VAR: 7W EPOCH YEAR: 1985								
2. PROFILE STARTS AT BULIT																					
3. FAC: 009.47 FAF: CABLE OM DIST FAF TO MAP: 3.52 THLD: 3.52																					
4. MIN. ALT: BULIT 3000, CABLE OM 2400																					
5. DIST TO THLD FROM OM: 3.52 MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: -																					
6. MIN GS INCPT: 2400 GS ALT AT: - OM: 2394 MM: - IM: -																					
7. GS ANGLE: 3.00 TCH: 53.4																					
8. MSA FROM: BSV VOR/DME 3100 (30 NM)																					
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		ILS: STANDARD			LOC: STANDARD									
CATEGORY =====>		A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
S-ILS 01**	1409	2400	200	1409	2400	200	1409	2400	200	1409	2400	200									
S-LOC 01	1600	2400	391	1600	2400	391	1600	2400	391	1600	4000	391									
CIRCLING	1760	1	534	1760	1	534	1760	1 1/2	534	1780	2	554									
NOTES: CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.																					
CITY AND STATE AKRON, OH			ELEVATION: 1226 TDZE: 1209 AIRPORT NAME: AKRON-CANTON RGNL				FACILITY IDENTIFIER: I-CAK		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 1, AMDT 38A 24 MAY 2018						SUP: AMDT: 38 DATED 01/13/2011						