

**Federal Aviation
Administration**

Transmittal Letter 18-12

April 20, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRA C	STATE	CITY	AIRPORT	FDC NUMB	FDC DATE	SUBJECT
24-May-18	MA	Hyannis	Barnstable Muni- Boardman/Polando Field	8/8564	4/11/18	RNAV (GPS) RWY 15, Orig-A

AIRAC Date: 24 MAY 2018

FDC **8/8564** HYA IAP BARNSTABLE MUNI-BOARDMAN/POLANDO FIELD, Hyannis, MA. RNAV (GPS) RWY 15, ORIG-A... LNAV VIS CAT C RVR 6000. CIRCLING VIS CAT C 1 5/8. DELETE NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA. CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA (NA WHEN USING CHATHAM ALTIMETER SETTING). DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHATHAM ALTIMETER SETTING AND INCREASE ALL DA 33 FEET AND ALL MDA 40 FEET. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHATHAM ALTIMETER SETTING: INCREASE ALL DAS 33 FEET; INCREASE ALL MDAS 40 FEET AND VISIBILITY LNAV CATS C AND D AND CIRCLING CAT C 1/8 SM. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHANGE NOTE: PROCEDURE NA FOR ARRIVALS AT BOS VOR/DME ON V141 NORTHEAST BOUND TO READ NORTHWEST BOUND. THIS IS RNAV (GPS) RWY 15, ORIG-B. 1803271849-PERM