

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
DREAR (IAF)	PEBIY (NOPT) (FB)	013.26 / 15.49	3000	LNAV: RW08	
RANDO (IAF)	PEBIY (NOPT) (FB)	157.60 / 6.04	3000	CLIMB TO 3000 DIRECT CORIR AND HOLD.	
PEBIY (IF/AF)	GOPBE (FB)	080.53 / 6.01	2700	ADDITIONAL FLIGHT DATA: HOLD E, RT, 260.93 INBOUND. CHART FAS OBST: 1059 TREE 432556N/0884321W CHART VDP AT 1.27 MILES TO RW08. GOPBE TO RW08: 3.05/40.	

- PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- HOLD W PEBIY, RT, 080.53 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 080.63 FAF: GOPBE DIST FAF TO MAP: 5.47 THLD: 5.47
- MIN. ALT: PEBIY 3000, GOPBE 2700
- DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
- MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
- GS ANGLE: _____ TCH: 34:1 IS CLEAR
- MSA FROM: RW08 2700

MAG VAR: 1W

EPOCH YEAR: 1995

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A			STANDARD @					
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1320	1	407	1320	1	407	1320	1 1/4	407		NA				
CIRCLING	1440	1	506	1440	1	506	1440	1 1/2	506		NA				

NOTES:
CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE DANE COUNTY REGIONAL-TRUAX FIELD
ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CHART NOTE: DME/DME RNP-0.3 NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RANDO VIA V9-341 NORTHEAST BOUND AND VIA V170

CONTINUED ON PAGE 2

CITY AND STATE JUNEAU, WI	ELEVATION: 934 TDZE: 913 AIRPORT NAME: DODGE COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, ORIG MAY 10 2007	SUP: AMDT: NONE DATED
------------------------------	---	---------------------------------	---	-----------------------------

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.**NORTHWEST BOUND.****CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.****CHART NOTE: VDP NA WHEN USING DANE COUNTY REGIONAL-TRUAX FIELD ALTIMETER SETTING.**

CITY AND STATE

JUNEAU, WI

ELEVATION: 934 TDZE: 913

AIRPORT NAME:

DODGE COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 8, ORIG

MAY 10 2007

SUP:

AMDT:

DATED:

NONE



RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	04 A

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	DREAR	DREAR	010	IAF	IF		FB				
	DREAR	PEBIY	020		TF		FB	1.0	013.3 (012T)	015.5	03000
	RANDO	RANDO	010	IAF	IF		FB				
	RANDO	PEBIY	020		TF		FB	1.0	157.6 (157T)	006.0	03000
	PEBIY	PEBIY	010		HF	R	FB		080.5 (080T)	005.0	03000
		PEBIY	010	FACF	IF		FB				03000
		GOPBE	020	FAF	TF		FB	0.5	080.5 (080T)	006.0	02700
		RW08	030	MAP	TF		FO	0.3	080.6 (080T)	005.5	00930

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	080.6 (080T)		01320
	CORIR	050		DF		FO	1.0			03000
	CORIR	060		HM	R	FO	2.0	260.9 (260T)	005.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CORIR	N432802.47	W0882332.51	N4328.041	W08823.542
	DREAR	N430817.19	W0890259.70	N4308.287	W08902.995
	GOPBE	N432430.88	W0885022.66	N4324.515	W08850.378
	PEBIY	N432325.65	W0885829.05	N4323.428	W08858.484
	RANDO	N432858.42	W0890146.53	N4328.974	W08901.776
	RW08	N432529.76	W0884259.59	N4325.496	W08842.993

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW08	00890	40

CITY AND STATE
JUNEAU, WIELEVATION: 934 TDZE: 913
AIRPORT NAME:
DODGE COUNTYFACILITY
IDENTIFIER:
RNAVPROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 8, ORIG
MAY 10 2007SUP:
AMDT: NONE
DATED: