

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.23

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> W99	<u>PROCEDURE NAME</u> VOR/DME -A	<u>ORIGINAL/AMENDMENT</u> 2D	<u>CITY</u> PETERSBURG	<u>STATE</u> WV		
<u>AIRPORT ELEVATION</u> 963	<u>TDZE</u>	<u>SUPERSEDED</u> VOR/DME-A	<u>ORIGINAL/AMENDMENT</u> 2C	<u>DATED</u> 06/17/2021	<u>MAG VAR</u> 6W	<u>EPOCH YEAR</u> 1965
<u>FACILITY</u> ESL	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 15 JUNE 2023	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
ESL VOR/DME	IF/IAF	EJOCU/ESL 8.00 DME					213.21	8.00	4000

MISSED APPROACH

MAP:

WUKVO/ESL 15.59 DME

MISSED APPROACH INSTRUCTIONS:

CLIMBING LEFT TURN TO 5000 DIRECT ESL VOR/DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD NE ESL VOR/DME, LT, 213.00 INBOUND, 5000 FT. IN LIEU OF PT (IAF), MAX 14000.
3. FAF: 213.21 FAF: EJOCU/ESL 8.00 DME DIST FAF TO MAP: DIST FAF TO THLD:
4. MIN ALT: ESL VOR/DME 5000, EJOCU/ESL 8.00 DME 4000, GNATT/ESL 13.00 DME 3500
8. MSA FROM: ESL VOR/DME 140-320 6100, 320-140 4600

EQUIPMENT REQUIREMENTS NOTES:

NOTES:

CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON ESL VOR/DME AIRWAY RADIALS 061 CW 103.



ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON.
FAS OBST: 2519 AAO 390151N/0790523W.
FAC CROSSES MIDPOINT OF RWY 13-31.

MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ CAT A, B 2200-2, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
CIRCLING	3100	1 1/4	2137	3100	1 1/2	2137		NA			NA				

- CHANGES - REASONS**
- 1. REMOVED CAT C MINIMUMS - PER FPT/ATC
 - 2. ADDED CAT A/B 2200 - 2 NA WHEN LOCAL WEATHER NOT AVAILABLE - IAW 8260.19I PARA 8-6-11 PARA B(4)
 - 3. REMOVED 7.59 DISTANCE FROM FAF TO MAP - NOT REQUIRED

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZDC, APT MGR

FLIGHT CHECKED BY
PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

DEVELOPED BY
ROSE BOONE-WALT

APPROVED BY
JASON KRETSCHMER

Digitally signed by
ROSE BOONE-WALT
Feb 10, 2023

Digitally signed by
JASON KRETSCHMER
Feb 21, 2023

OFFICE
AJV-A421

OFFICE
AJV-A421

OFFICE
AJV-A421

DATE
02/01/2023

DATE
Feb 21, 2023

Digitally signed by
JASON KRETSCHMER
Feb 21, 2023

TITLE
MANAGER

