

**Federal Aviation
Administration**

Transmittal Letter 21-06

January 22, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
2/25/2021	KS	Norton	Norton Muni	0/6672	1/5/2021	RNAV (GPS) RWY 16, Amdt 1A

25 FEBRUARY 2021

FDC 0/6672 NRN IAP NORTON MUNI, NORTON, KS. RNAV (GPS) RWY 16, AMDT 1A... PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C (2F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C OR ABOVE 54C. DELETE NOTE: WHEN LOCAL ALTIMETER NOT RECEIVED, USE HILL CITY MUNI ALTIMETER SETTING AND INCREASE ALL DA 86 FEET, ALL MDA 100 FEET, INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS, LNAV CAT C VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER NOT RECEIVED, USE HILL CITY MUNI ALTIMETER SETTING AND INCREASE LPV DA TO 2720 FEET, LNAV/VNAV DA TO 2742 FEET, ALL MDA 100 FEET, LNAV CAT C VISIBILITY 1/4 SM, CIRCLING CAT C VISIBILITY 1/2 SM. ALTERNATE MINIMUMS: STANDARD, NA WHEN LOCAL WEATHER NOT AVAILABLE. LNAV CAT C VISIBILITY 1 3/8 SM. CIRCLING CAT C MDA 3100/HAA 716, CAT C VIS 2. THIS IS RNAV (GPS) RWY 16, AMDT 1B. 2011302029-PERM