

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
TERMINAL ROUTES				MISSED APPROACH				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW09 CLIMBING RIGHT TURN TO 2600 DIRECT EON VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 181.00 INBOUND. CHART FAS OBST: 909 TREE 412254N/0874116W CHART 1017 TOWER 412259N/0874651W. AGREE TO RW09: 3.04/40. CHART LANSING AWOS-3, 119.275.				
CGT VORTAC	NABYO (FB)	262.39 / 16.26	2300					
NABYO (IAF)	HOSIX (NOPT) (FB)	182.53 / 5.00	2300					
OCEDO (IAF)	HOSIX (NOPT) (FB)	015.89 / 5.13	2300					
HOSIX (IF/IAF)	AGREE (FB)	092.53 / 6.10	2300					
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD W HOSIX, RT, 092.53 INBOUND, 2300 FT. IN LIEU OF PT (IAF) 3. FAC: 092.62 FAF: AGREE DIST FAF TO MAP: 4.56 THLD: 4.56 4. MIN. ALT: HOSIX 2300, AGREE 2300, SEFOB/2.50 NM TO RW09 1620 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW09 2800				MAG VAR: 3W EPOCH YEAR: 2010				
MINIMUMS								
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: NA	X			
CATEGORY =====>	A		B		C		D	
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	1220	1	430	1220	1	430	1220	1 1/4
CIRCLING	1260	1	470	1260	1	470	1260	1 1/2
NOTES: CHART NOTE: CIRCLING TO RWY 27 NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CGT VORTAC VIA V8 EASTBOUND. SEE 8260-10								
CITY AND STATE		ELEVATION: 790 TDZE: 790		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:
MONEE, IL		AIRPORT NAME:				RNAV (GPS) RWY 9, ORIG		AMDT: NONE
		BULT FIELD				12 MAR 2009		DATED

 QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

**CHART NOTE: USE LANSING MUNI ALTIMETER SETTING; WHEN NOT RECEIVED, USE CHICAGO MIDWAY INTL
ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.**

CITY AND STATE

MONEE, IL

ELEVATION: 790 TDZE: 790

AIRPORT NAME:

BULT FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 9, ORIG

12 MAR 2009

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

M

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	CGT	CGT	010		IF		FB				
	CGT	NABYO	020	IAF	TF		FB	2.0	262.4 (259T)	016.3	02300
	CGT	HOSIX	030		TF		FB	1.0	182.5 (180T)	005.0	02300
	HOSIX	HOSIX	010		HF	R	FB		092.5 (090T)	004.0	02300
	OCEDO	OCEDO	010	IAF	IF		FB				
	OCEDO	HOSIX	020		TF		FB	1.0	015.9 (013T)	005.1	02300
		HOSIX	010	FACF	IF		FB				02300
		AGREE	020	FAP	TF		FB	0.5	092.5 (090T)	006.1	02300
		SEFOB	021	SDP	TF		FB	0.3	092.6 (090T)	002.1	0162001643
		RW09	030	MAP	TF		FO	0.3	092.6 (090T)	002.5	00830

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	EON	040		DF	R	FO	1.0			02600
	EON	050		HM	R	FO	2.0	181.0 (178T)	004.0	02600

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CGT	N413036.02	W0873417.56	N4130.600	W08734.293
	EON	N411610.72	W0874727.75	N4116.179	W08747.463
	AGREE	N412236.95	W0874723.16	N4122.616	W08747.386
	HOSIX	N412234.26	W0875529.47	N4122.571	W08755.491
	NABYO	N412734.41	W0875532.74	N4127.574	W08755.546
	OCEDO	N411734.16	W0875700.67	N4117.569	W08757.011
	SEFOB	N412237.73	W0874439.14	N4122.629	W08744.652
	RW09	N412238.59	W0874119.89	N4122.643	W08741.332

RUNWAY DATA	THRESHOLD	
	RWY	ELEVATION TCH
RW09	00790 40	

CITY AND STATE
MONEE, IL

ELEVATION: 790 TDZE: 790
AIRPORT NAME:
BULT FIELD

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 9, ORIG
12 MAR 2009

SUP:
AMDT: NONE
DATED: