

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
PRYOR INT (40E)	EGOYI (TF) (FB) (40E)	061.10 / 28.56	3000	LNAV: RW13											
EOS VOR/DME (40V)	OSUYA (TF) (FB) (40E)	193.83 / 18.79	3000												
RZC VORTAC (40V)	HUMTI (TF) (FB) (40E)	297.48 / 28.02	3000	CLIMBING LEFT TURN TO 3000 DIRECT HUMTI AND HOLD											
EGOYI (IAF) (40E) (43A)	HUMTI (TF) (FB) (NOPT) (40E) (41E)	041.31 / 5.00	3000												
OSUYA (IAF) (40E) (43A)	HUMTI (TF) (FB) (NOPT) (40E) (41E)	221.39 / 5.00	3000	ADDITIONAL FLIGHT DATA: FAS OBST: 1409 TREE 362018N / 0942709W CHART: 1740 TOWER 362554N/ 0943047W RIROY TO RW13: 3.05/40 ROUTE TYPE DESCRIPTION: A, P APCH ROUTE QUALIFIER 2: S											
HUMTI (IF/IAF) (40E) (43I)	RIROY (TF) (FB) (40E) (43F)	131.35 / 6.01	3000												
RW13 (MAP) (40G) (41Y) (43M)	1580 MSL (CA) (42M)	131.40													
1580 MSL	HUMTI (DF) (FO) (40E) (41E) (43H)		3000												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)				MAG VAR: 3E EPOCH YEAR: 05											
2. HOLD NW HUMTI, RT, 131.35 INBOUND, 3000 FT IN LIEU OF PT (IAF) (40E) (41E) (43C)															
3. FAC: 131.40 FAF: RIROY DIST FAF TO MAP: 5.58 THLD: 5.58															
4. MIN. ALT: HUMTI 3000, RIROY 3000															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR															
8. MSA FROM: RW13 3400															
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A	X									
CATEGORY =====>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	1720	1	544	1720	1	544	1720	1 1/2	544		NA				
CIRCLING	1820	1	640	1820	1	640	1860	2	680		NA				
NOTES: DME/DME RNP-0.3 NA CHART NOTE: USE FAYETTEVILLE/ NORTHWEST ARKANSAS REGIONAL ALTIMETER SETTING; IF NOT RECEIVED, USE JOPLIN, MO ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (CONTINUED ON PAGE 2)															
CITY AND STATE			ELEVATION: 1180 TDZE: 1176			FACILITY IDENTIFIER:			PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:			SUP:			
DECATUR, AR			AIRPORT NAME: CRYSTAL LAKE			RNAV			MAY 12 2005 RNAV (GPS) RWY 13, ORIG			AMDT: NONE			
												DATE			

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CHART PLANVIEW NOTES:

PROCEDURE NA FOR ARRIVAL AT PRYOR INT VIA V-15 SOUTHWEST BOUND, V-140 WEST BOUND

PROCEDURE NA FOR ARRIVAL ON EOS VOR/DME AIRWAY RADIALS 150 CW 248

PROCEDURE NA FOR ARRIVAL ON RZC VORTAC AIRWAY RADIALS 264 CW 333

CITY AND STATE

DECATUR, AR

ELEVATION: 1180 TDZE: 1176

AIRPORT NAME:

CRYSTAL LAKE

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

MAY 12 2005
RNAV (GPS) RWY 13, ORIG

SUP:

AMDT: NONE

DATED: