

**Federal Aviation
Administration**

Transmittal Letter 24-12

April 12, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/16/2024	NE	Lincoln	Lincoln	4/7349	3/18/2024	ILS Y OR LOC Y RWY 18, Amdt 7C

AIRAC Date: 16 MAY 2024

FDC 4/7349 LNK IAP LINCOLN, LINCOLN, NE. ILS Y OR LOC Y RWY 18, AMDT 7C... DELETE ALTERNATE
MISSED APPROACH. CIRCLING MDA/HAA CAT C: 1820/601; CAT D 1960/741, VIS CAT D 2 1/2. ROROC FIX
MINIMUMS CIRCLING MDA/HAA CAT C: 1820/601; CAT D 1960/741, VIS CAT D 2 1/4. CHANGE: BACKUP
ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE BEATRICE
ALTIMETER SETTING AND INCREASE DA TO 1486; AND ALL MDA 100 FEET, INCREASE VISIBILITY S-LOC
18 CAT C/D/E AND CIRCLING CATS C AND D 1/4 SM; INCREASE ROROC FIX MINIMUMS S-LOC 18 CAT
C/D/E VISIBILITY 3/8 SM AND CIRCLING CATS C AND D 1/4 SM. THIS IS ILS Y OR LOC Y RWY 18, AMDT 7D.
2403141720-PERM