

U.S. Department of Transportation Federal Aviation Administration		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES								MISSED APPROACH							
FROM	TO	COURSE AND DISTANCE			ALTITUDE	LNAV: RW23 CLIMBING LEFT TURN TO 4000 DIRECT GAGTE WP AND HOLD ADDITIONAL FLIGHT DATA: FAS OBST: 165 TREE 591906/1555300 HOLD SW, RT, 034.71 INBOUND JADAM TO RW23: 3.04/40 CHART VDP AT 1.32 NM TO RW23 * FINAL SEGMENT: (TF) CHART MRL 5/23 MAG VAR: 19E EPOCH YEAR: 00									
NUTUW WP (IAF)	CEKIT WP (TF) (FB)	200.68/13.45			2700										
GAGTE WP (IAF)	CEKIT WP (TF) (FB)	321.05/10.63			2700										
CEKIT WP	JADAM WP (TF) (FB)	233.29/6.00			1800										
RW23 (MAP)	440 MSL (CA)	233.13													
440 MSL	GAGTE WP (DF) (FO)				4000										
THIS IS A CORRECTED COPY OF A PROCEDURE PUBLISHED IN TL 03-22. PROCEDURE NA FOR ARRIVALS AT NUTUW VIA V427 NORTHBOUND															
1. PT NA SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT CEKIT WP 3. FAC: 233.13 FAF: JADAM WP DIST FAF TO MAP: _____ THLD: 5.22 4. MIN. ALT: CEKIT WP 2700, JADAM WP 1800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS CLEAR 8. MSA FROM: RW23 3800															
MINIMUMS															
TAKEOFF:	<input checked="" type="checkbox"/> STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT		ALTERNATE: N A		<input checked="" type="checkbox"/>									
CATEGORY =====>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	440	1	350	440	1	350		NA			NA				
CIRCLING	520	1	430	540	1	450		NA			NA				
NOTES: GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE ILIAMNA ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET PROCEDURE NA AT NIGHT *VDP NA WITH ILIAMNA ALTIMETER SETTING															
CITY AND STATE		ELEVATION: 90 TDZE: 90		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:					
IGIUGIG, AK		AIRPORT NAME: IGIUGIG		RNAV		OCT 30 2003 RNAV (GPS) RWY 23, ORIG				AMDT: NONE					
										DATE					