

**Federal Aviation
Administration**

Transmittal Letter 8-11

April 6, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
24-May-18	NC	Lincolnton	Lincolnton-Lincoln County Rgnl	7/7045	3/29/18	ILS Y OR LOC Y RWY 23, Orig-A

AIRAC Date: 24 MAY 2018

FDC 7/7045 IPJ IAP LINCOLNTON-LINCOLN COUNTY RGNL, Lincolnton, NC. ILS Y OR LOC Y RWY 23, ORIG-A... GATEQ FIX MINIMUMS: CIRCLING CAT A MDA 1400/HAA 522, CAT B MDA 1420/HAA 542. CHART NOTE: RWY 23 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLOTTE ALTIMETER SETTING: INCREASE DA TO 1212 FEET AND VISIBILITY 1/8 SM; INCREASE ALL MDAS 80 FEET AND VISIBILITY S-LOC 23 CATS C/D 1/8 SM AND CIRCLING CATS C/D 1/4 SM AND GATEQ FIX MINIMUMS CATS C/D 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLOTTE ALTIMETER SETTING AND INCREASE ALL DA 63 FEET AND ALL MDA 80 FEET; INCREASE S-LOC 23 CATS C/D VISIBILITY 1/8 MILE, INCREASE S-ILS 23 ALL CATS AND CIRCLING CATS C/D VISIBILITY 1/4 MILE, INCREASE GATEQ FIX MINIMUMS S-LOC 23 CATS C/D AND CIRCLING CATS C/D VISIBILITY 1/4 MILE. THIS IS ILS Y OR LOC Y RWY 23, ORIG-B. 1712191228-PERM