

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**

TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KFHB	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 22	<u>ORIGINAL/AMENDMENT</u> 1E	<u>CITY</u> FERNANDINA BEACH	<u>STATE</u> FL		
<u>AIRPORT ELEVATION</u> 16	<u>TDZE</u> 16	<u>SUPERSEDED</u> RNAV (GPS) RWY 22	<u>ORIGINAL/AMENDMENT</u> 1D	<u>DATED</u> 12/05/2019	<u>MAG VAR</u> 5W	<u>EPOCH YEAR</u> 2000
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 3 DECEMBER 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TAA

FROM	FIX TYPE	TO	FIX TYPE	ALTITUDE
1. 131/30 CW 311/30	NOPT	131/4 CW 311/4		3000
2. 131/4 CW 311/4		EZDAW	IF/IAF	2000
3. 311/30 CW 041/30		HEVIP	IAF	3000
4. 041/30 CW 131/30		041/10 CW 131/10		4000
5. 041/10 CW 131/10		IFWOC	IAF	3000

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
HEVIP	IAF	EZDAW	NOPT	TF	FB	1.00	310.69	6.00	2000
IFWOC	IAF	EZDAW	NOPT	TF	FB	1.00	130.59	6.00	2000
EZDAW	IF/IAF	CUGTO		TF	FB	1.00	220.64	6.65	2000
CUGTO	FAF	FIVBA/3.10 NM TO RW22		TF	FB	0.30	220.62	2.75	
FIVBA/3.10 NM TO RW22		RW22	MAP	TF	FO	0.30	220.62	3.10	
RW22	MAP	600 MSL		CA			220.62		0600
600 MSL		EZDAW		DF	FO	1.00			2000



CHANGES - REASONS

1. REMOVED LPV AND LNAV/VNAV MINIMUMS. - RUNWAY SURVEY FAILED PER FPT.
2. REMOVED NOTE "FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15°C OR ABOVE 54°C". - LNAV/VNAV MINIMUMS NA.
3. UPDATED PROFILE NOTE "VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET})" TO "VGSI AND DESCENT ANGLE NOT COINCIDENT (VGSI {ANGLE}/TCH {FEET})". - APV MINIMUMS REMOVED.
4. LNAV ONLY NOTE REMOVED FROM ADDITIONAL FLIGHT DATA. - LNAV AND CIRCLING MINIMUMS PUBLISHED ONLY.
5. REMOVED NOTE BARO-VNAV NA WHEN USING JACKSONVILLE INTL ALTIMETER SETTING. - LNAV/VNAV MINIMUMS REMOVED.
6. UPDATED ALTIMETER NOTE FROM "WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JACKSONVILLE INTL ALTIMETER SETTING AND INCREASE LPV DA TO 354 FEET, LNAV/VNAV DA 453 FEET, AND ALL MDA 40 FEET; INCREASE LNAV CATS C/D VISIBILITY 1/4 SM AND CIRCLING CAT C VISIBILITY 1/4 SM." TO " WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JACKSONVILLE INTL ALTIMETER AND INCREASE ALL MDA 40 FEET: INCREASE LNAV CATS C/D VISIBILITY 1/4 SM AND CIRCLING CAT C VISIBILITY 1/4 SM". - LPV AND LNAV/VNAV MINIMUMS REMOVED.
7. ALL CHANGES FROM AMDT 1A THRU 1D HAVE BEEN INCORPORATED INTO THIS PROCEDURE.

COORDINATED WITH:

A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒ **OTHER:** ZJX, JAX APP CON, AMGR

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJF-10) MEMO, APRIL 29, 2020, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

DATE

DEVELOPED BY

NICHOLAS K. JACKSON

Digitally signed by

NICHOLAS JACKSON

DONALD H LANIER

Sep 23, 2020

OFFICE

AJV-A431

DATE

07/14/2020

APPROVED BY

LONNIE EVERHART

Digitally signed by
DONALD H LANIER

Sep 23, 2020

OFFICE

AJV-A430

DATE

TITLE
MANAGER