

**Federal Aviation  
Administration**

**Transmittal Letter 08-15**

**June 13, 2008**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

«AIRAC_ DATE»	«STATE»	«CITY»	«AIRPORT»	«FDC_NUMBER»	«FDC_ DATE»	«SUBJECT»
5/31/08	NV	LAS VEGAS	NORTH LAS VEGAS	8/9213		ILS OR LOC RWY 12L, ORIG-A

**AIRAC Date: 31 MAY 2008**

FDC 8/9213 VGT FI/P NORTH LAS VEGAS, LAS VEGAS, NV. ILS OR LOC RWY 12L, ORIG-A... S-ILS 12L DA 2456/HAT 267 CATS A/B, VIS CATS A/B 1. DELETE NOTE: IF LOCAL ALTIMETER SETIING NOT RECEIVED, USE MCCARRAN INTL ALTIMETER SETIING AND INCREASE DA TO 2412, AND ALL MDA 40 FEET. CHART NOTE: WHEN LOCAL ALTIMETER SETIING NOT RECEIVED, USE MCCARRAN INTL ALTIMETER SETTING AND INCREASE DA TO 2478 AND VISIBILITY CATS A/B 1/4 MILE; INCREASE ALL MDA 40 FEET. ALTERNATE MINIMUMS STANDARD (POUND). (POUND) NA WHEN CONTROL TOWER CLOSED. THIS IS ILS OR LOC RWY 12L, ORIG-B.