

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW02R CLIMB TO 1300 THEN CLIMBING LEFT TURN TO 3000 DIRECT NUELG AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 150.93 INBOUND. CHART FAS OBST: 987 BLDG 415018N/0881541W. CHART 1187 TOWER 414827N/0881607W. DISTANCE TO THLD FROM 250 HAT: 0.63 NM. WAAS CHANNEL # 45531 REFERENCE PATH ID: W02A LTP HAE: 195.5 M									
PLANO		CEXAB (TF) (FB) (RNP 2.00)			087.91 / 8.09			3000											
CEXAB (IAF)		GIDVE (NOPT) (TF) (FB) (RNP 1.00)			050.92 / 7.00			3000											
JOT VOR/DME (IAF)		GIDVE (NOPT) (TF) (FB) (RNP 1.00)			001.69 / 8.90			3000											
GIDVE (IF/IAF)		HEGBI (TF) (FB) (RNP 1.00)			014.97 / 6.94			2500											
HEGBI (FAF)		RW02R (MAP) (TF) (FO) (RNP 0.30)			014.99 / 5.34														
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S GIDVE, RT, 014.97 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 014.99 FAF: HEGBI DIST FAF TO MAP: 5.34 THLD: 5.34 4. MIN. ALT: GIDVE 3000, HEGBI 2500 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2500 GS ALT AT: HEGBI 2500 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS CLEAR 8. MSA FROM: RW02R 3400																MAG VAR: 1W		EPOCH YEAR: 1985	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	1001	1	250	1001	1	250	1001	1	250	1001	1	250							
LNAV/VNAV DA	1111	1 1/8	360	1111	1 1/8	360	1111	1 1/8	360	1111	1 1/8	360							
LNAV MDA	1240	1	489	1240	1	489	1240	1 3/8	489	1240	1 3/8	489							
CIRCLING	1260	1	501	1260	1	501	1360	1 3/4	601	1360	2	601							
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AURORA ALTIMETER SETTING AND INCREASE ALL DA 37 FEET AND ALL MDA 40 FEET; INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE AND LNAV CAT C/D (CONTINUED ON PAGE 2)																			
CITY AND STATE		ELEVATION: 759 TDZE: 751			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:						
CHICAGO/WEST CHICAGO, IL		AIRPORT NAME:						RNAV (GPS) RWY 2R, ORIG-D					AMDT: ORIG-C						
		DUPAGE						29 MARCH 2018					DATED 02/04/2016						

QUALITY
 16
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW02R (MAP)	1300 MSL (CA)	014.99	1300
1300 MSL	NUELG (DF) (FO) (RNP 1.00)		3000

NOTES, (CONT.):

VISIBILITY 1/8 MILE.

CHART NOTE: VDP AND BARO-VNAV NA WHEN USING AURORA ALTIMETER SETTING.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON JOT VOR/DME AIRWAY RADIALS 314 CW 328.

CHART NOTE: CIRCLING RWY 15, 28, 33 NA AT NIGHT.

QUALITY
16
CHECKED

CITY AND STATE

CHICAGO/WEST CHICAGO, IL

ELEVATION: 759

TDZE: 751

AIRPORT NAME:

DUPAGE

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 2R, ORIG-D

29 MARCH 2018

SUP:

AMDT: ORIG-C

DATED: 02/04/2016

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KDPA
RUNWAY	RW02R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W02A
LTP/FTP LATITUDE	415336.0745N
LTP/FTP LONGITUDE	0881459.7135W
LTP/FTP ELLIPSOIDAL HEIGHT	+01955
FPAP LATITUDE	415502.5600N
FPAP LONGITUDE	0881430.8200W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0784
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 4D10A117

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02287
FPAP ORTHOMETRIC HEIGHT	+02287

QUALITY
16
CHECKED

CITY AND STATE CHICAGO/WEST CHICAGO, IL	ELEVATION: 759 AIRPORT NAME: TDZE: 751 DUPAGE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 2R, ORIG-D 29 MARCH 2018	SUP:
				AMDT: ORIG-C
				DATED: 02/04/2016