

**Federal Aviation
Administration**

Transmittal Letter 18-12

April 20, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMB	FDC DATE	SUBJECT
24-May-18	OK	Ardmore	Ardmore Muni	7/5213	4/6/18	RNAV (GPS) RWY 31, Amdt 1B

AIRAC Date: 24 MAY 2018

F FDC **7/5213** ADM IAP ARDMORE MUNI, Ardmore, OK. RNAV (GPS) RWY 31, AMDT 1B... LPV DA 991/HAT 258, VISIBILITY 1 ALL CATS. LNAV VISIBILITY 1 MILE ALL CATS, CIRCLING MDA CAT C 1440/HAA 663. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ARDMORE DOWNTOWN EXECUTIVE ALTIMETER SETTING: INCREASE LPV DA TO 1026 FEET; INCREASE LNAV/VNAV DA TO 1276 FEET AND ALL VISIBILITIES 3/8 SM; INCREASE ALL MDAS 40 FEET AND CIRCLING CATS C AND D VISIBILITY 1/4 SM. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LPV, ALL CATS AND LNAV CATS A AND B. CHART NOTE: WHEN USING ARDMORE DOWNTOWN EXECUTIVE ALTIMETER SETTING, INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS AND LNAV CATS A AND B. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV CATS C AND D VISIBILITY TO 1-3/8 SM. CHART NOTE: FOR INOPERATIVE ALS, WHEN USING ARDMORE DOWNTOWN EXECUTIVE ALTIMETER SETTING, INCREASE LNAV CATS C AND D TO 1-3/8 SM. CHART NOTE: VDP NA WHEN USING ARDMORE DOWNTOWN EXECUTIVE ALTIMETER SETTING. CHART NOTE: RWY 31 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: RWY 13, 35 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: CIRCLING RWY 13, 35 NA AT NIGHT. DELETE NOTE: NIGHT LANDING: RWY 13, 35 NA. DELETE NOTE: FOR INOP MALSR WHEN USING ARDMORE DOWNTOWN EXECUTIVE ALTIMETER SETTING, INCREASE LNAV CATS C AND D VISIBILITY TO 1

3/8 MILES. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ARDMORE DOWNTOWN EXECUTIVE ALTIMETER SETTING AND INCREASE ALL DA 35 FEET AND ALL MDA 40 FEET; INCREASE LNAVNAV ALL CATS AND LNAV CATS C AND D VISIBILITY 1/8 MILE, AND CIRCLING CAT D VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) RWY 31, AMDT 1C. 1708181212-PERM.