

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.23**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> AND <u>AIRPORT ELEVATION</u> 782 <u>FACILITY</u> ELW	<u>PROCEDURE NAME</u> VOR RWY 5 <u>TDZE</u> 759 <u>COORDINATES OF FACILITIES</u>	<u>SUPERSEDED</u> VOR RWY 5	<u>ORIGINAL/AMENDMENT</u> 10C <u>ORIGINAL/AMENDMENT</u> 10B <u>ACTUAL EFFECTIVE DATE</u> 5 SEPTEMBER 2024	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CITY</u> ANDERSON <u>DATED</u> 02/27/2020	<u>MAG VAR</u> 0E <u>CANCEL/SUSPEND</u>	<u>STATE</u> SC <u>EPOCH YEAR</u> 1975
---	--	--------------------------------	--	---	---	---	---

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
-------------	-----------------	-----------	-----------------	-----------------	--------------	------------	---------------	-----------------	-----------------

MISSED APPROACH

MAP:

5.38 NM AFTER ELW VORTAC OR AT 5.38 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1600 THEN CLIMBING LEFT TURN TO 2500 DIRECT ELW VORTAC AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2. HOLD SW ELW VORTAC, RT, 043.73 INBOUND, 2500 FT. IN LIEU OF PT (IAF), MAX 6000.					
3. FAC: 039.36	FAF: ELW VORTAC	DIST FAF TO MAP: 5.38	DIST FAF TO THLD: 5.38		
4. MIN ALT:					
8. MSA FROM: ELW VORTAC 3000					

NOTES:

CHART NOTE: RWY 17, 35 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CEU ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND S-05 VISIBILITY CAT C/D 1/8 SM, AND CIRCLING VISIBILITY CAT C/D 1/4 SM.
CHART NOTE: VDP NA WHEN USING CEU ALTIMETER SETTING.
CHART NOTE: CIRCLING RWY 17, 35 NA AT NIGHT.

ADDITIONAL FLIGHT DATA:

ELW VORTAC TO RW05: 2.98/49

CHART FAS OBST: 846 TRANSMISSION_LINE (45-020441) 342921N/0824320W.
CHART VDP AT 4.13 DME.
DISTANCE VDP TO THLD 1.25 NM.
CHART CIRCLING ICON.



MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-05	1200	1/2	441	1200	1/2	441	1200	7/8	441	1200	7/8	441			
CIRCLING	1260	1	478	1320	1	538	1440	1 3/4	658	1500	2 1/4	718			

CHANGES - REASONS

1. INCORPORATED P NOTAMS 7/7107 AND 9/2016 (10A / 10B).
2. REMOVED SEGMENT HARTI TO ELW VORTAC. – ODF VORMON AND FPT REQUEST.
3. ADDITIONAL FLIGHT DATA: CHANGED “CHART FAS OBST: 890 T-L TWR 342835N/0824334W” TO “CHART FAS OBST: 846 TRANSMISSION_LINE (45-020441) 342921N/0824320W” – NEW FINAL CONTROLLING OBST.
4. NOTES: CHANGED “CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLEMSON ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET.” TO “CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CEU ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND S-05 VISIBILITY CAT C/D 1/8 SM, AND CIRCLING VISIBILITY CAT C/D 1/4 SM” – NEW INOP TABLE RESULTS.
5. MINIMUMS: CHANGED S-5 CAT C AND D VIS FROM “¾ AND 1” TO “7/8”. – IAW 8260.3E TABLE 3-1-1
6. PROFILE LINE 2: ADDED "MAX 6000" - IAW 8260.19I 8-5-2
7. TDZE CHANGED FROM 758 TO 759 - AIRNAV DATA PULL.
8. MINIMUMS: ALTERNATE CHANGED FROM "STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE." TO " STANDARD - CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE." - IAW 8260.19I
9. NOTES: CHANGED "CHART NOTE: VDP NA WHEN USING CLEMSON ALTIMETER SETTING." TO "CHART NOTE: VDP NA WHEN USING CEU ALTIMETER SETTING."- IAW 8260.19I
10. ADDITIONAL FLIGHT DATA: CHANGED "CHART VDP AT 4.12 DME" TO "CHART VDP AT 4.13 DME". - 8260.3E FORMULA 2-6-5.
11. MINIMUMS: S-05 HAT ALL CATS CHANGED FROM "442" TO "441" - TDZE CHANGED FROM "758" TO "759".

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZTL, GSP APP CON, AMGR

FLIGHT CHECKED BY

MICHAEL W PENDERGRASS

Digitally signed by

ERIC N SUSKI

Jul 24, 2024

OFFICE

FPO

DATE

07/23/2024

DEVELOPED BY

ERIC N SUSKI (ZACHARY KRUEGER)

Digitally signed by

ERIC N SUSKI

Jun 07, 2024

OFFICE

AJV-A431

DATE

05/06/2024

APPROVED BY

ERIC N SUSKI

Digitally signed by

ERIC N SUSKI

Jun 07, 2024

OFFICE

AJV-A431

DATE

TITLE

MANAGER

